

LV HRC fuse base Sz. 3, 1-pole 630 A 690 V (1000 V) flat terminal



Model	
Product brand name	SETRON
Product designation	LV HRC fuse system
Design of the thread / of the connection screw	M12
Design of the product	LV HRC fuse base
General technical data	
Number of poles	1
Size of fuse system / acc. to DIN EN 60269-1	NH3
Usage category	Without
circuit-breaker / Design	3NH34
Supply voltage	
Operating current / at AC / rated value	630 A
Supply voltage	
• at AC / rated value	690 V
• at DC	440 V
Current	
Tripping residual / rated value / derated current / at 40 Cel	580 A

Product details	
Product component / Swivel mechanism	No
Maximum short-circuit current breaking capacity (Icu)	
• at AC / rated value	120 kA
• at DC / rated value	25 kA

Connections	
Tightening torque / with screw-type terminals / maximum	38 N·m
Type of electrical connection	With flat-type terminal
• for main current circuit	flat connector

Mechanical Design	
Mounting type	fixed mounting
Mounting type	
• bus-mounting	No
Net weight	1 079 g

Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	Test Certificates
 CSA	 EG-Konf.	Special Test Certificate Type Test Certificates/Test Report

Shipping Approval	other
 GL	Environmental Conformations Miscellaneous

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NH3430
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NH3430
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NH3430

CAX-Online-Generator
<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>