SIEMENS

Data sheet

6GK5008-0GA10-1AB2

SCALANCE XB008G unmanaged Industrial Ethernet Switch for 10/100/1000 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V DC power supply, with 8x 10/100/1000 Mbit/s RJ45 ports electrical Manual available as a download



Product type designation	SCALANCE XB008G
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
 for network components or terminal equipment 	8; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	0
Interfaces / other	
Number of electrical connections	
 for power supply 	1
Type of electrical connection	
 for power supply 	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V

• external / minimum	19.2 V
external / maximum	28.8 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.52 A
Power loss [W]	
• at DC / at 24 V	12.5 W
	12.0 W
Ambient conditions	
Ambient temperature	
 during operation 	-10 +60 °C
 during storage 	-40 +80 °C
• during transport	-40 +80 °C
Relative humidity	
 at 25 °C / without condensation / during 	95 %
operation / maximum	
Protection class IP	IP20
Design dimensions and unights	
Design, dimensions and weights Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.26 kg
Mounting type	0.20 kg
35 mm DIN rail mounting	Yes
wall mounting	Yes
•	
 S7-1500 rail mounting 	No
Product functions / management, configuration, eng	gineering
Product function	
multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No
Product functions / redundancy Product function	
	Yes
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	
 Parallel Redundancy Protocol 	No
(PRP)/Redundant Network Access (RNA)	
Standards, specifications, approvals	
Standards, specifications, approvais Standard	

• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
 for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
 for emitted interference 	EN 61000-6-4 (Class B)
• for interference immunity	EN 61000-6-2
MTBF	112 у

Standards,	specifications,	approvals / CE
Certificate	of suitability / CE	marking

EN 61000-6-2, EN 61000-6-4
Yes
Yes

Yes

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
 to website: Industrial communication 	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx Download Manager 	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

03/11/2020