

Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 55 mm Bar thickness: 5.10 mm+TT profile for contactor with overload relay 3R, S2 with 1 DIN rail 35 mm, up to 56 A Length 182 mm



Model	
Product brand name	SETRON
Product designation	Device adapter
Design of the product	Accessories
Design of support rail	1 mounting rail, 35 mm
Operating current / at AC / rated value	56 A
Operating voltage / at AC / rated value	690 V
Suitability for use	S2 with overload relay 3RT
Mechanical Design	
Width	55 mm
Length	182 mm
Busbar center-to-center spacing	60 mm
Net weight	232 g
Certificates	

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA	 UR		 EG-Konf.	Special Test Certificate	Miscellaneous
Shipping Approval			other		
 ABS	 PRS	 RINA	Miscellaneous		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1261-5FM08>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1261-5FM08>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1261-5FM08

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

