



Load feeder fuseless, Reversing duty 400 V AC, Size S00 0.45...0.63  
A 230 V AC screw terminal for 60 mm busbar systems (also fulfills  
type of coordination 1) Type of coordination 2, I<sub>q</sub> = 150 kA 1 NC  
(contactor)

|                                                                                                                                                                                                                                                       |                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product brand name                                                                                                                                                                                                                                    | SIRIUS                                                                                                                                                            |
| Product designation                                                                                                                                                                                                                                   | Reversing starter                                                                                                                                                 |
| Design of the product                                                                                                                                                                                                                                 | for 60 mm busbars                                                                                                                                                 |
| Product type designation                                                                                                                                                                                                                              | 3RA22                                                                                                                                                             |
| Manufacturer's article number                                                                                                                                                                                                                         |                                                                                                                                                                   |
| <ul style="list-style-type: none"> <li>• of the supplied contactor</li> <li>• of the supplied circuit-breakers</li> <li>• of the supplied RS assembly kit</li> <li>• of the supplied busbar adapter</li> <li>• of the supplied link module</li> </ul> | <a href="#">3RT2015-1AP02</a><br><a href="#">3RV2011-0GA10</a><br><a href="#">8US1250-5AS10</a><br><a href="#">8US1251-5DS10</a><br><a href="#">3RA1921-1DA00</a> |

| General technical data                                                                           |              |
|--------------------------------------------------------------------------------------------------|--------------|
| Size of the circuit-breaker                                                                      | S00          |
| Size of load feeder                                                                              | S00          |
| Insulation voltage                                                                               |              |
| <ul style="list-style-type: none"> <li>• with degree of pollution 3 at AC rated value</li> </ul> | 690 V        |
| Surge voltage resistance rated value                                                             | 6 kV         |
| Protection class IP                                                                              |              |
| <ul style="list-style-type: none"> <li>• on the front</li> <li>• of the terminal</li> </ul>      | IP20<br>IP20 |

|                                                                   |                   |
|-------------------------------------------------------------------|-------------------|
| <b>Shock resistance</b>                                           |                   |
| • acc. to IEC 60068-2-27                                          | 6g / 11 ms        |
| <b>Mechanical service life (switching cycles)</b>                 |                   |
| • of contactor typical                                            | 30 000 000        |
| <b>Type of assignment</b>                                         | 2                 |
| <b>Type of protection according to ATEX directive 2014/34/EU</b>  | Ex II (2) GD      |
| Certificate of suitability according to ATEX directive 2014/34/EU | DMT 02 ATEX F 001 |

|                                    |                |
|------------------------------------|----------------|
| <b>Ambient conditions</b>          |                |
| <b>Temperature compensation</b>    | -20 ... +60 °C |
| Relative humidity during operation | 10 ... 95 %    |

|                                                                                   |                   |
|-----------------------------------------------------------------------------------|-------------------|
| <b>Main circuit</b>                                                               |                   |
| <b>Number of poles for main current circuit</b>                                   | 3                 |
| <b>Design of the switching contact</b>                                            | electromechanical |
| <b>Adjustable pick-up value current of the current-dependent overload release</b> | 0.45 ... 0.63 A   |
| <b>Operating voltage</b>                                                          |                   |
| • rated value                                                                     | 690 V             |
| • at AC-3 rated value maximum                                                     | 690 V             |
| <b>Operating frequency rated value</b>                                            | 50 ... 60 Hz      |
| <b>Operating current</b>                                                          |                   |
| • at AC-3                                                                         |                   |
| — at 400 V rated value                                                            | 0.6 A             |
| <b>Operating power</b>                                                            |                   |
| • at AC-3                                                                         |                   |
| — at 400 V rated value                                                            | 180 W             |

|                                                      |         |
|------------------------------------------------------|---------|
| <b>Control circuit/ Control</b>                      |         |
| <b>Type of voltage of the control supply voltage</b> | AC      |
| <b>Control supply voltage at AC</b>                  |         |
| • at 50 Hz rated value                               | 230 V   |
| • at 60 Hz rated value                               | 230 V   |
| <b>Apparent holding power of magnet coil at AC</b>   | 4.2 V·A |

|                                           |     |
|-------------------------------------------|-----|
| <b>Auxiliary circuit</b>                  |     |
| <b>Product extension Auxiliary switch</b> | Yes |

|                                            |                      |
|--------------------------------------------|----------------------|
| <b>Protective and monitoring functions</b> |                      |
| <b>Trip class</b>                          | CLASS 10             |
| <b>Design of the overload release</b>      | thermal (bimetallic) |

|                                                         |        |
|---------------------------------------------------------|--------|
| <b>UL/CSA ratings</b>                                   |        |
| <b>Full-load current (FLA) for three-phase AC motor</b> |        |
| • at 480 V rated value                                  | 0.63 A |

| Short-circuit protection                                                                                                                                                                                                                                                                                                                                                                                                               |                                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>Product function Short circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                       | Yes                                    |
| <b>Design of the short-circuit trip</b>                                                                                                                                                                                                                                                                                                                                                                                                | magnetic                               |
| <b>Conditional short-circuit current (I<sub>q</sub>)</b>                                                                                                                                                                                                                                                                                                                                                                               |                                        |
| <ul style="list-style-type: none"> <li>at 400 V acc. to IEC 60947-4-1 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                           | 150 000 A                              |
| Installation/ mounting/ dimensions                                                                                                                                                                                                                                                                                                                                                                                                     |                                        |
| <b>Mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                               | vertical                               |
| <b>Mounting type</b>                                                                                                                                                                                                                                                                                                                                                                                                                   | for snapping onto 60 mm busbar systems |
| <b>Height</b>                                                                                                                                                                                                                                                                                                                                                                                                                          | 200 mm                                 |
| <b>Width</b>                                                                                                                                                                                                                                                                                                                                                                                                                           | 90 mm                                  |
| <b>Depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                           | 156 mm                                 |
| <b>Required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                |                                        |
| <ul style="list-style-type: none"> <li>for grounded parts <ul style="list-style-type: none"> <li>forwards 32 mm</li> <li>Backwards 0 mm</li> <li>upwards 50 mm</li> <li>at the side 10 mm</li> <li>downwards 10 mm</li> </ul> </li> <li>for live parts <ul style="list-style-type: none"> <li>forwards 32 mm</li> <li>Backwards 0 mm</li> <li>upwards 50 mm</li> <li>downwards 10 mm</li> <li>at the side 10 mm</li> </ul> </li> </ul> |                                        |
| Connections/ Terminals                                                                                                                                                                                                                                                                                                                                                                                                                 |                                        |
| <b>Type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                   |                                        |
| <ul style="list-style-type: none"> <li>for main current circuit</li> </ul>                                                                                                                                                                                                                                                                                                                                                             | screw-type terminals                   |
| Safety related data                                                                                                                                                                                                                                                                                                                                                                                                                    |                                        |
| <b>B10 value</b>                                                                                                                                                                                                                                                                                                                                                                                                                       |                                        |
| <ul style="list-style-type: none"> <li>with high demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                               | 1 000 000                              |
| <b>Proportion of dangerous failures</b>                                                                                                                                                                                                                                                                                                                                                                                                |                                        |
| <ul style="list-style-type: none"> <li>with high demand rate acc. to SN 31920</li> </ul>                                                                                                                                                                                                                                                                                                                                               | 73 %                                   |
| Certificates/ approvals                                                                                                                                                                                                                                                                                                                                                                                                                |                                        |

| General Product Approval | For use in hazardous locations | Declaration of Conformity |
|--------------------------|--------------------------------|---------------------------|
|--------------------------|--------------------------------|---------------------------|



CSA



UL



ATEX



EG-Konf.

[Miscellaneous](#)

| Test Certificates | Marine / Shipping |
|-------------------|-------------------|
|-------------------|-------------------|

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



ABS



BUREAU  
VERITAS



LRS



PRS

| Marine / Shipping | other | Railway |
|-------------------|-------|---------|
|-------------------|-------|---------|



RINA



RMRS



DNV-GL  
DNVGL.COM/AF

[Confirmation](#)

[Vibration and Shock](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2210-0GD15-2AP0>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2210-0GD15-2AP0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2210-0GD15-2AP0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2210-0GD15-2AP0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2210-0GD15-2AP0&lang=en)


### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RA2210-0GD15-2AP0/char>

### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2210-0GD15-2AP0&objecttype=14&gridview=view1>







last modified:

04/07/2020