



Load feeder fuseless, Reversing duty 400 V AC, Size S0 27.0...32.0 A 230 V AC screw terminal for installation on standard mounting rail with standard mounting rail adapter (also fulfills type of coordination 1) Type of coordination 2, I<sub>q</sub> = 150 kA 1 NO+1 NC (contactor)

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Product brand name                 | SIRIUS                              |
| Product designation                | Reversing starter                   |
| Design of the product              | for standard rail or screw mounting |
| Product type designation           | 3RA22                               |
| Manufacturer's article number      |                                     |
| • of the supplied contactor        | <a href="#">3RT2027-1AP00</a>       |
| • of the supplied circuit-breakers | <a href="#">3RV2021-4EA10</a>       |
| • of the supplied RH assembly kit  | <a href="#">3RA2923-1BB1</a>        |
| • of the supplied link module      | <a href="#">3RA2921-1AA00</a>       |

| General technical data                         |       |
|------------------------------------------------|-------|
| Size of the circuit-breaker                    | S0    |
| Size of load feeder                            | S0    |
| Insulation voltage                             |       |
| • with degree of pollution 3 at AC rated value | 690 V |
| Surge voltage resistance rated value           | 6 kV  |
| Protection class IP                            |       |
| • on the front                                 | IP20  |
| • of the terminal                              | IP20  |
| Shock resistance                               |       |

|                                                                   |                   |
|-------------------------------------------------------------------|-------------------|
| • acc. to IEC 60068-2-27                                          | 6g / 11 ms        |
| <b>Mechanical service life (switching cycles)</b>                 |                   |
| • of contactor typical                                            | 10 000 000        |
| <b>Type of assignment</b>                                         | 2                 |
| <b>Type of protection according to ATEX directive 2014/34/EU</b>  | Ex II (2) GD      |
| Certificate of suitability according to ATEX directive 2014/34/EU | DMT 02 ATEX F 001 |

#### Ambient conditions

|                                    |                |
|------------------------------------|----------------|
| <b>Temperature compensation</b>    | -20 ... +60 °C |
| Relative humidity during operation | 10 ... 95 %    |

#### Main circuit

|                                                                                   |                   |
|-----------------------------------------------------------------------------------|-------------------|
| <b>Number of poles for main current circuit</b>                                   | 3                 |
| <b>Design of the switching contact</b>                                            | electromechanical |
| <b>Adjustable pick-up value current of the current-dependent overload release</b> | 27 ... 32 A       |
| <b>Operating voltage</b>                                                          |                   |
| • rated value                                                                     | 690 V             |
| • at AC-3 rated value maximum                                                     | 690 V             |
| <b>Operating frequency rated value</b>                                            | 50 ... 60 Hz      |
| <b>Operating current</b>                                                          |                   |
| • at AC-3                                                                         |                   |
| — at 400 V rated value                                                            | 29 A              |
| <b>Operating power</b>                                                            |                   |
| • at AC-3                                                                         |                   |
| — at 400 V rated value                                                            | 15 000 W          |

#### Control circuit/ Control

|                                                      |         |
|------------------------------------------------------|---------|
| <b>Type of voltage of the control supply voltage</b> | AC      |
| <b>Control supply voltage at AC</b>                  |         |
| • at 50 Hz rated value                               | 230 V   |
| <b>Apparent holding power of magnet coil at AC</b>   | 9.8 V·A |

#### Auxiliary circuit

|                                           |     |
|-------------------------------------------|-----|
| <b>Product extension Auxiliary switch</b> | Yes |
|-------------------------------------------|-----|

#### Protective and monitoring functions

|                                       |                      |
|---------------------------------------|----------------------|
| <b>Trip class</b>                     | CLASS 10             |
| <b>Design of the overload release</b> | thermal (bimetallic) |

#### UL/CSA ratings

|                                                         |      |
|---------------------------------------------------------|------|
| <b>Full-load current (FLA) for three-phase AC motor</b> |      |
| • at 480 V rated value                                  | 14 A |
| <b>Yielded mechanical performance [hp]</b>              |      |
| • for three-phase AC motor                              |      |

|                            |       |
|----------------------------|-------|
| — at 220/230 V rated value | 10 hp |
| — at 460/480 V rated value | 20 hp |
| — at 575/600 V rated value | 25 hp |

#### Short-circuit protection

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>Product function Short circuit protection</b>         | Yes       |
| <b>Design of the short-circuit trip</b>                  | magnetic  |
| <b>Conditional short-circuit current (I<sub>q</sub>)</b> |           |
| • at 400 V acc. to IEC 60947-4-1 rated value             | 150 000 A |

#### Installation/ mounting/ dimensions

|                          |                                                                           |
|--------------------------|---------------------------------------------------------------------------|
| <b>Mounting position</b> | vertical                                                                  |
| <b>Mounting type</b>     | On adapter for screw and snap-on mounting on 35 mm standard mounting rail |
| <b>Height</b>            | 265 mm                                                                    |
| <b>Width</b>             | 90 mm                                                                     |
| <b>Depth</b>             | 120 mm                                                                    |
| <b>Required spacing</b>  |                                                                           |
| • for grounded parts     |                                                                           |
| — forwards               | 32 mm                                                                     |
| — Backwards              | 0 mm                                                                      |
| — upwards                | 50 mm                                                                     |
| — at the side            | 10 mm                                                                     |
| — downwards              | 10 mm                                                                     |
| • for live parts         |                                                                           |
| — forwards               | 32 mm                                                                     |
| — Backwards              | 0 mm                                                                      |
| — upwards                | 50 mm                                                                     |
| — downwards              | 10 mm                                                                     |
| — at the side            | 10 mm                                                                     |

#### Connections/ Terminals

|                                      |                      |
|--------------------------------------|----------------------|
| <b>Type of electrical connection</b> |                      |
| • for main current circuit           | screw-type terminals |

#### Safety related data

|                                          |           |
|------------------------------------------|-----------|
| <b>B10 value</b>                         |           |
| • with high demand rate acc. to SN 31920 | 1 000 000 |
| <b>Proportion of dangerous failures</b>  |           |
| • with high demand rate acc. to SN 31920 | 73 %      |

#### Certificates/ approvals

|                          |                                |                           |
|--------------------------|--------------------------------|---------------------------|
| General Product Approval | For use in hazardous locations | Declaration of Conformity |
|--------------------------|--------------------------------|---------------------------|



CSA



UL



ATEX



EG-Konf.

[Miscellaneous](#)

|                   |                   |
|-------------------|-------------------|
| Test Certificates | Marine / Shipping |
|-------------------|-------------------|

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



ABS



BUREAU  
VERITAS



LRS



PRS

|                   |       |         |
|-------------------|-------|---------|
| Marine / Shipping | other | Railway |
|-------------------|-------|---------|



RINA



RMRS



DNVGL.COM/AF

[Confirmation](#)

[Vibration and Shock](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2220-4EB27-0AP0>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2220-4EB27-0AP0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2220-4EB27-0AP0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2220-4EB27-0AP0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2220-4EB27-0AP0&lang=en)


### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RA2220-4EB27-0AP0/char>

### Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2220-4EB27-0AP0&objecttype=14&gridview=view1>







last modified:

04/07/2020