



Creating Safe Work Solutions During COVID-19

MQDEC-401SS

▶ DOUBLE-ENDED CORDSETS



Euro-style Quick Disconnect Cable
Double-ended 4-pin Male Connector Straight
4-pin Female Connector Straight 0.3 m Length
Chrome plated brass coupling nut
Part Number: 15103

CERTIFICATIONS



SPECIFICATIONS

Number of Contacts	4
Number of Connectors	2
Cable Jacket Material	PVC
Cable Jacket Color	Black
Connector Body Material/Color	PUR Black
Outside Cable Diameter (mm)	5.9
Cordset Length (m)	0.31
Trunk Length (m)	No Trunk
Shield/No Shield	No Shield
Coupling Material/Color	Nickel Plated Brass
Maximum Temp. (°C)	105
Current Rating (A)	4.0
Minimum Temp. (°C)	-40
Voltage Rating (V)	250 V ac/dc
IP Rating	IP67
Primary Connector Type	EURO
Primary Coupling Method	M12 Single Key
Primary Gender	Female
Primary Orientation	Straight
Primary Number of Conductors	5
Primary AWG	22

Secondary Connector Type	EURO
Secondary Coupling Method	M12 Single Key
Secondary Gender	Male
Secondary Orientation	Straight
Secondary Number of Conductors	4
Secondary AWG	22
Feature: Hazardous Area	No
Oil/Grease Resistant	No

COMPATIBLE PRODUCTS



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America