

Crimping pliers - CRIMPFOX-P CK 1.6 ER 2.5 OIC-L - 1069228

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, for rolled contacts CK 1,6-ER... OIC, cross section: 0.14 ... 2.5 mm². Unlockable pressure lock, precise parallel crimping, front entry, B crimp, incl. positioning tool

Your advantages

- Precision-manufactured dies ensure consistently high levels of quality during contact processing
- High crimping force with low manual force
- Marked die stations for precise processing of corresponding cross sections
- Parallel motion sequences of the dies for symmetrical and optimum crimping results
- The integrated positioning tool ensures that the contacts are perfectly aligned

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 743936
GTIN	4055626743936
Weight per Piece (excluding packing)	497.500 g
Custom tariff number	82032000
Country of origin	Sweden
Note	Made to Order (non-returnable)

Technical data

Dimensions

Length (b)	233 mm
------------	--------

General

Compression	B crimp
Designation	Crimping position 1
Min. cross section	0.75 mm ²
Max. cross section	1 mm ²
AWG max	18
Designation	Crimping position 2
Max. cross section	2.5 mm ²
AWG max	14

Crimping pliers - CRIMPFOX-P CK 1.6 ER 2.5 OIC-L - 1069228

Technical data

General

Designation	Crimping position 3
Max. cross section	1.5 mm ²
AWG max	16
Die station	Crimping position 4
Min. cross section	0.34 mm ²
Max. cross section	0.5 mm ²
AWG min	22
AWG max	20
Weight	450 g
Min. cross section	0.14 mm ²
Max. cross section	2.5 mm ²

Classifications

eCl@ss

eCl@ss 10.0.1	21043811
eCl@ss 6.0	21043800
eCl@ss 7.0	21043811
eCl@ss 9.0	21043811

ETIM

ETIM 6.0	EC000168
ETIM 7.0	EC000168

Accessories

Accessories

Crimp contact

Crimp contact - CK1,6-ER-1,00BU OIC AG - 1004362



Crimp contact, contact diameter: 1.6 mm, rolled, Socket, contact material: Cu alloy, nickel-plated, contact surface: silver-plated, connection cross section: 0.34 mm² ... 1 mm² AWG 22 ... 17

Crimp contact - CK1,6-ER-1,00ST OIC AG - 1004360



Crimp contact, contact diameter: 1.6 mm, rolled, Pin, contact material: Cu alloy, nickel-plated, contact surface: silver-plated, connection cross section: 0.34 mm² ... 1 mm² AWG 22 ... 17

Crimping pliers - CRIMPFOX-P CK 1.6 ER 2.5 OIC-L - 1069228

Accessories

Crimp contact - CK1,6-ER-2,50BU OIC AG - 1004366



Crimp contact, contact diameter: 1.6 mm, rolled, Socket, contact material: Cu alloy, nickel-plated, contact surface: silver-plated, connection cross section: 1.5 mm² ... 2.5 mm² AWG 16 ... 14

Crimp contact - CK1,6-ER-2,50ST OIC AG - 1004365



Crimp contact, contact diameter: 1.6 mm, rolled, Pin, contact material: Cu alloy, nickel-plated, contact surface: silver-plated, connection cross section: 1.5 mm² ... 2.5 mm² AWG 16 ... 14
