

Olympic Wire and Cable

7 Madison Road • Fairfield, NJ 07004

973.227.7996 800.526.2269 • Fax: 973.227.1606

email: sales@olympicwire.com

Olympic P/N 5267, RG213/U Broadcast & Computer Coaxial**SPECIFICATIONS**

RG Type	213/U
Conductor	13 AWG 7/21 Bare Copper
Insulation	Solid Polyethylene
Nom. Insulation Thickness	0.020 in
Shielding	80% Bare Copper Braid
Nom. Core O.D.	0.285 in
Jacket	Non-Contaminating PVC -Type 11A
Nom. O.D.	0.405 in
UL Style	CM
Nom. Attenuation	0.2 db/100 ft at 1 MHz 0.6 db/100 ft at 10 MHz 1.3 db/100 ft at 50 MHz 1.9 db/100 ft at 100 MHz 2.7 db/100 ft at 200 MHz 4.1 db/100 ft at 400 MHz 6.5 db/100 ft at 700 MHz 7.6 db/100 ft at 900 MHz 8.0 db/100 ft at 1000 MHz 21.5 db/100 ft at 4000 MHz
Nom. Velocity of Propagation	83%
Nominal Capacitance	16.2 pF/ft
Nominal Impedance	50 ohms
Operating Temperature	80 °C

RoHS Compliant



RoHS Compliant