

Conductor marker carrier - PATG HF 2/30 - 1014055

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 30 x 4 mm

Your advantages

- ✓ The PATG HF... sleeve is a captive marker carrier
- ✓ The corresponding UCT-WMT... and UC-WMT... insert labels are used for marking
- ✓ Due to the plastic properties of the PATG HF..., high-quality fluid printing of the UC-WMT... with the BLUEMARK... is required
- ✓ These conductor marking systems consist of marker carriers and insert labels
- ✓ The use of high-quality plastics supports the most stringent demands of the rail industry and the automotive industry
- ✓ Comprehensive approvals ensure international use

Key Commercial Data

Packing unit	500 pc
Minimum order quantity	500 pc
GTIN	 4 046356 779425
GTIN	4046356779425
Weight per Piece (excluding packing)	0.660 g
Custom tariff number	39269097
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Length (b)	30 mm
Width (a)	6.4 mm
Cable diameter	2 mm ... 4 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

Conductor marker carrier - PATG HF 2/30 - 1014055

Technical data

General

Color	transparent/black
Type	Profile
Components	free from silicone, halogen, and cadmium
Material	TPU
RoHS compliant	Yes
Marking mounting type	slide-on
Result	Test passed
Oxygen index (DIN EN ISO 4589-2)	33%
Class I	4
Class F	1
R22	HL 1 - HL 3
R23	HL 1 - HL 3
R24	HL 1 - HL 3

Classifications

eCl@ss

eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27149100
eCl@ss 7.0	27149153
eCl@ss 8.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 5.0	EC002248
ETIM 6.0	EC001530
ETIM 7.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504

Conductor marker carrier - PATG HF 2/30 - 1014055

Classifications

UNSPSC

UNSPSC 20.0	39131504
UNSPSC 21.0	39131504