

Conductor marker carrier - PATG HF 3/12 - 1014057

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 12 x 4 mm

Your advantages

- ✓ The PATG HF... sleeve is a captive marker carrier
- ✓ The corresponding UCT-WMT... and UC-WMT... insert labels are used for marking
- ✓ Due to the plastic properties of the PATG HF..., high-quality fluid printing of the UC-WMT... with the BLUEMARK... is required
- ✓ These conductor marking systems consist of marker carriers and insert labels
- ✓ The use of high-quality plastics supports the most stringent demands of the rail industry and the automotive industry
- ✓ Comprehensive approvals ensure international use

Key Commercial Data

| | |
|--------------------------------------|--------------------------------|
| Packing unit | 500 pc |
| Minimum order quantity | 500 pc |
| GTIN | |
| GTIN | 4046356779449 |
| Weight per Piece (excluding packing) | 0.300 g |
| Custom tariff number | 39269097 |
| Country of origin | Germany |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| | |
|----------------|---------------|
| Length (b) | 12 mm |
| Width (a) | 8.9 mm |
| Cable diameter | 4 mm ... 7 mm |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 85 °C |
|---------------------------------|------------------|

Conductor marker carrier - PATG HF 3/12 - 1014057

Technical data

General

| | |
|----------------------------------|--|
| Color | transparent/black |
| Type | Profile |
| Components | free from silicone, halogen, and cadmium |
| Material | TPU |
| RoHS compliant | Yes |
| Marking mounting type | slide-on |
| Result | Test passed |
| Oxygen index (DIN EN ISO 4589-2) | 33% |
| Class I | 4 |
| Class F | 1 |
| R22 | HL 1 - HL 3 |
| R23 | HL 1 - HL 3 |
| R24 | HL 1 - HL 3 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27061700 |
| eCl@ss 4.1 | 27061700 |
| eCl@ss 5.0 | 27400400 |
| eCl@ss 5.1 | 27400400 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149153 |
| eCl@ss 8.0 | 27400401 |
| eCl@ss 9.0 | 27400401 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC002248 |
| ETIM 6.0 | EC001530 |
| ETIM 7.0 | EC001530 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |

Conductor marker carrier - PATG HF 3/12 - 1014057

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |