

Overview		
Specifications		

Details

Specifications

1

Agency Approvals	UL and CSA
Brand	Scotchlok™
Color Family	Blue
Conductor Size	0.5 - 1.5 mm²
Conductor Sizes	22 - 14 AWG
Connection Type	Pigtail
Connector Style	Insulation Displacement
CSA File Number	LR15503
Family	IDC for Electrical Applications
Flame	Yes

	Retardant	
	Insulation Material	Nylon
	Insulation Outer Diameter (Imperial)	0.150 Inch
Overview Specifications Details	Insulation Outer Diameter (Metric)	3.8 mm
	Material	Flame Retardant Nylon
	Maximum Operating Temperature (Celsius)	105 Degree Celsius
	Maximum Operating Temperature (Fahrenheit)	221 Degree Fahrenheit
	Maximum Recommended Voltage Rating	600 V
	Maximum Wire Gauge	14 AWG
	Minimum Wire Gauge	22 AWG
	Package Quantity	50
	Packaging	Box

Product Color

Blue

	Product Type	Connectors
	RoHS 2011/65/EU Compliant	Yes
Overview	RoHS EU Comments	RoHS 2011/65/EU compliant without exemption *Important RoHS information
Specifications Details	TDS Required	Yes
bound	UL File Number	E23438
	Voltage Application	Low Voltage
	Water- resistant	Yes
	Wire Connector Type	IDC Connectors
	Wire Gauge	22 to 14 AWG
	-	
	D · (· !! ·	

Details

 Blue cap and white body nyloninsulated connector is suitable to connect

- Overview Specifications Details
- Accommodates 22 to 14 AWG solid/stranded
 UL Listed, CSA Certified

and RoHS

resistance

2 or 3

•

wires Brass

for corrosion

element construction for good conductivity and tin plating

2011/65/EU Compliant 3M™ Scotchlok™ Insulation Displacement Connector 314 provides а dual element connection and moisture resistant seal with а mineral oil based grease.

Overview Specifications Details

> resistant. ЗМ™ Scotchlok™ Insulation Displacement Connector 314 is 600V rated for building wire and 1000V rated for signs, fixtures and luminaires. lt withstands temperatures of 221 degrees F r (105 degrees C). UL

The connector is nylon insulated and used to connect

2 or 3

is self

and moisture

wires. It

stripping, flame retardant Listed, CSA Certified and RoHS 2011/65/EU Compliant.

Legal Disclaimer

Manufacturing Origin: USA

Overview

Specifications

Details

The designation that а product is Manufactured in the USA means the product undergoes substantial transformation in one of our U.S. Manufacturing plants. Some products . contain imported components. Note: 3M products . offered on а government contract that

require country of origin representation must be certified by 3M Trade Compliance. Contact customer service at 800-245-3573 to request a

certificate.

