

## Crimping tool, pneumatic - ZAP 100 - 1203259

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Pneumatic crimping pliers, for ferrules in accordance with DIN 46228-1: 1992-08 and DIN 46228-4: 1990-09, for conductor cross section 4 - 10 mm<sup>2</sup>

### Your advantages

- ✓ These crimping pliers are pneumatic tools for ferrules with a cross section range of 0.25 to 10 mm<sup>2</sup>



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 018146
GTIN	4017918018146
Weight per Piece (excluding packing)	711.800 g
Custom tariff number	84671900
Country of origin	Germany
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Length (b)	200 mm
Width (a)	44 mm
Height (c)	44 mm
Stripping length	0 mm

#### General

Compression	trapezoidal
Min. AWG, flexible, multi-strand	8
AWG max., flexible, multi-strand	12
Pressure range	4 bar ... 6 bar
Air consumption per compression	0.2 l

# Crimping tool, pneumatic - ZAP 100 - 1203259

## Technical data

### General

Power consumption	0 W
Weight	0.4 kg
Min. cross section	4 mm <sup>2</sup>
Max. cross section	10 mm <sup>2</sup>

## Classifications

### eCl@ss

eCl@ss 10.0.1	17130101
eCl@ss 4.0	21040300
eCl@ss 4.1	21040300
eCl@ss 5.0	21040300
eCl@ss 5.1	17130100
eCl@ss 6.0	17130100
eCl@ss 7.0	17130101
eCl@ss 8.0	17130101
eCl@ss 9.0	17130101

### ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC000168
ETIM 6.0	EC002778
ETIM 7.0	EC002778

### UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518
UNSPSC 18.0	27111518
UNSPSC 19.0	27111518
UNSPSC 20.0	27111518
UNSPSC 21.0	27111518

## Approvals

### Approvals

## Crimping tool, pneumatic - ZAP 100 - 1203259

### Approvals

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		RU C- DE.A*30.B.01744
-----	---	--------------------------

---