

8-Port Rack-Mount PDU with C13 Outlets - 16 A - 10 ft. Power Cord (NEMA5-20p) - 1U

Product ID: PDU08C13H



This rack-mount PDU features eight C13 outlets and you can install it into 1U of rack space to power your rack-mount equipment. The PDU provides 16 amps of power to be shared across the eight outlets.

Sleek, professional installation

Unlike some rack power solutions that mount awkwardly, if at all, this rack-mount PDU is EIA-310D compliant, which ensures a secure and tidy installation into any 19" rack with 1U of available space. Mounting screws and cage nuts are also included to ensure you have everything you need, saving you time and hassle.

Flexible power solution

For maximum compatibility with your devices, this PDU features C13 outlets which are ideal for a wide range of globally distributed devices including I.T equipment, office equipment, measuring instruments and medical devices. Plus, with a total of eight C13 outlets, the PDU can distribute power to your entire rack.

Protects your equipment

In the event of random energy surges that can occur during power outages or other anomalies, this PDU prevents costly damages to your equipment with a built-in dual circuit breaker, ensuring your equipment is protected.

The housing of this PDU is also constructed of rugged steel to provide maximum durability in any environment.

The PDU08C13H is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Add eight easily accessible power outlets to your rack
- Provide power to rack-mounted equipment with C13 power plugs

Features

- Ensure hassle-free installation with a 1U EIA-310D compliant PDU
- Get wide device compatibility with a PDU that features C13 outlets
- 10 ft. (3 m) C19 to NEMA5-20p power cord included
- Protect your equipment with the dual circuit breaker that's built into this PDU
- Solid steel chassis for durability
- 1U rack-mount design

Hardware	Warranty	2 Years
	Form Factor	Horizontal
	Number of Power Outlets	8
	Rack-Mountable	Yes
Performance	Load Capacity	1920 VA
	Maximum Output Voltage	240V
	Maximum Total Current	20A
	Maximum Total Current Draw per Phase	20A
	Nominal Input Voltage	110V - 240V
	Nominal Output Voltage	110V - 240V
	Phase Power	Single phase power adapter
	Power Cord Included	10 ft [3 m] C19 to NEMA5-20p
	Regulatory Derated Input Current (North America)	16A
Surge Protection	3600 Joules	
Connector(s)	Input Connector(s)	1 - IEC C20 (16A, 3 conductor) Power Plug Input
	Output Connectors	8 - IEC C13 (10A, 3 conductor) Power Receptacle Receptacle Output
Power	Input Voltage	110V-240V AC
Physical Characteristics	Product Height	1.7 in [4.4 cm]
	Product Length	3.9 in [10 cm]
	Product Width	18.9 in [48 cm]
	Weight of Product	4.9 lb [2.2 kg]
Packaging Information	Package Height	3.2 in [82 mm]
	Package Length	21.7 in [55 cm]
	Package Width	7.5 in [19 cm]
	Shipping (Package) Weight	5.4 lb [2.4 kg]
What's in the Box	Included in Package	1 - rack-mount PDU
		1 - 10 ft [3 m] C19 to NEMA5-20p power cord
		4 - M5 screws
		4 - M5 cage nuts

1 - instruction manual

Product appearance and specifications are subject to change without notice.