

4 Port Dual Monitor DVI KVM Switch - Dual Screen Display Compact USB KVM Switch with Integrated USB 3.0 Hub & Audio - Dual View KVM - Dell HP Apple Lenovo - TAA Compliant

Product ID: SV431DD2DU3A



The TAA compliant Dual-Monitor DVI KVM Switch controls four multimedia computer systems from one dual-DVI monitor workstation.

Increase Productivity

The KVM switch supports four separate multimedia computer systems and the use of a dual DVI-D single-link monitor workstation, increasing productivity by enabling you to access more information at once.





Integrated USB 3.0 Hub

The 2-port hub that's built into the USB 3.0 KVM switch shares two additional peripherals (in addition to keyboard and mouse) among attached computers as if they were directly connected while supporting high-performance peripherals such as flash drives and video capture devices.

Full Multimedia Support

With support for separate stereo audio and microphones, the KVM switch box connects everything you need directly to your systems, saving you money and desk space.

Easy to Operate

The front-panel push-buttons make it easy to switch between systems and activate the auto-scan feature. The hotkey functionality makes accessing each system quickly, while an optional buzzer sound confirms the switch.

StarTech.com offers a wide selection of high-quality KVM switches and KVM-related products to help you access your systems more efficiently without the expense and clutter of extra keyboards, mice, and monitors. This 4-port DVI USB KVM switch is backed by a 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Small office
- Back office
- Medical office
- Repair shop

Features

- IMPROVE EFFICIENCY: 4 Port Dual Monitor DVI KVM Switch with hotkey and manual switching, to access 4 workstations or servers with USB and DVI video from a single keyboard, monitor, and mouse
- WORK SMARTER: Combines dual DVI displays and a high-speed 2-Port USB 3.0 hub to share USB devices between connected computers seamlessly; OS independent and works with video cards from NVIDIA and AMD
- TECH SPECS: 4 Port KVM | Dual Screen | DVI Single Link |
 2048x1536 Analog | 1920x1200 Digital | 2-Port USB 3.0 Hub |
 Hotkey, Push Button | OS Independent | Audio | Dual DVI + USB
 Console | TAA
- USER-FRIENDLY: Dual view KVM switch with compact & durable housing features easily accessible large push buttons on the front panel in addition to hotkey support; also provides audio and mic switching
- THE STARTECH.COM ADVANTAGE: This KVM is TAA compliant, and StarTech.com offers a 2-year warranty and free lifetime 24/5 multilingual technical support based in North America



Data Sheet

	Warranty	2 Years
Hardware	Audio	Yes
	Cables Included	No
	Daisy-Chain	No
	KVM Ports	4
	Number of Monitors Supported	2
	PC Interface	USB 3.0
	PC Video Type	DVI
	Rack-Mountable	No
Performance	Auto Scan	10, 20, 30, 40, 50, and 60 seconds
	DVI Support	Yes - Single Link
	Hot-Key Selection	Yes
	IP Control	No
	Maximum Analog Resolutions	2048 x 1536 @ 85Hz
	Maximum Data Transfer Rate	5 Gbps
	Maximum Digital Resolutions	1920 x 1200 @ 60Hz
	On-Screen Display	No
	On-Screen Display Port Selection Support	No Push Button and Hotkeys
	Port Selection Support	Push Button and Hotkeys
Connector(s)	Port Selection Support Supported Resolutions	Push Button and Hotkeys Minimum 640 x 480
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported	Push Button and Hotkeys Minimum 640 x 480 Yes
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported Console Interface(s)	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Output
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported Console Interface(s)	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Output 8 - DVI-I (29 pin) Female Input
Connector(s)	Port Selection Support Supported Resolutions Wide Screen Supported Console Interface(s)	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Output 8 - DVI-I (29 pin) Female Input 4 - 3.5 mm Mini-Jack (3 Position) Female Input
Connector(s) Indicators	Port Selection Support Supported Resolutions Wide Screen Supported Console Interface(s)	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Output 8 - DVI-I (29 pin) Female Input 4 - 3.5 mm Mini-Jack (3 Position) Female Input 4 - 3.5 mm Mini-Jack (3 Position) Female Output
	Port Selection Support Supported Resolutions Wide Screen Supported Console Interface(s) Host Connectors	Push Button and Hotkeys Minimum 640 x 480 Yes 2 - DVI-I (29 pin) Female Output 2 - USB Type-A (4 pin; HID Port) USB 1.1 Female Input 2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Female 1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - 3.5 mm Mini-Jack (3 Position) Female Output 8 - DVI-I (29 pin) Female Input 4 - 3.5 mm Mini-Jack (3 Position) Female Input 4 - 3.5 mm Mini-Jack (3 Position) Female Output 4 - 3.5 mm Mini-Jack (3 Position) Female Output 4 - USB 3.1 USB Type-B (9 pin, Gen 1, 5 Gbps) Female



Data Sheet

	Input Current	0.8A
	Input Voltage	100 - 240 AC
	Output Current	2A
	Output Voltage	9V DC
	Plug Type	М
	Power Consumption (In Watts)	18 W
	Power Source	AC Adapter Included
Environmental	Humidity	0~90% RH, Non-condensing
	Operating Temperature	0~40 degree C
	Storage Temperature	-20~60 degree C
Physical Characteristics	Color	Black
	Material	Steel
	Product Depth	3.9 in [100 mm]
	Product Height	2.6 in [6.6 cm]
	Product Length	0 in [0 mm]
	Product Width	10 in [25.3 cm]
	Weight of Product	2.9 lb [1.3 kg]
Packaging Information	Package Height	7.5 in [19.1 cm]
	Package Length	10.6 in [26.8 cm]
	Package Width	6.3 in [16 cm]
	Shipping (Package) Weight	10.6 oz [300 g]
What's in the Box	Included in Package	1 - KVM switch
		1 - universal power adapter (NA/JP, EU, UK, ANZ)
		1 - quick-start guide

Product appearance and specifications are subject to change without notice.