

# SPDIF Digital Coaxial or Toslink Optical to Stereo RCA Audio Converter

Product ID: SPDIF2AA



The SPDIF2AA Toslink/Optical SPDIF to RCA Audio Converter lets you convert a 2-channel Digital Coaxial or Toslink/Optical SPDIF input signal into an RCA analog stereo output.

Perfect for home and professional audio applications, this SPDIF to RCA audio converter saves the cost of upgrading equipment for compatible connections, and offers separate Digital Coax and Toslink inputs for dual-function conversion. The small form factor design makes it suitable for installation into virtually any location, regardless of space constraints, while still providing a lossless audio signal. Plus, the digital coaxial or Toslink to RCA converter supports plug-and-play installation, saving you time and hassle.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Connect newer Blu-Ray, DVD Players and Game Consoles to two channel analog stereo receivers
- Convert or extend your digital audio input into an analog format, without signal or quality loss

### Features

- Accepts Digital Coax or Toslink digital audio input
- Outputs analog L/R RCA stereo analog audio
- Compact form factor
- Easy to install and use
- 24-bit S/PDIF incoming bit stream
- Supports 32, 44.1, 48 and 96 KHz sampling rates

<b>Hardware</b>	Warranty	2 Years
	AV Input	Digital Coaxial Toslink
	AV Output	RCA Audio
<b>Performance</b>	Audio Specifications	2 channel (stereo) supported 32, 44.1, 48 and 96 KHz Sampling rates
<b>Connector(s)</b>	Connector A	1 - Digital Coax Audio (RCA) Female Input 1 - Toslink (SPDIF, Optical) Female Input
	Connector B	1 - Stereo Audio (2 x RCA) Female Output
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.5 A
	Input Voltage	100 - 240 AC
	Output Current	2.0 A
	Output Voltage	5 DC
	Plug Type	N
	Power Consumption (In Watts)	0.5
	Power Source	AC Adapter Included
<b>Environmental</b>	Humidity	10~85 % RH Non-Condensing
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-10°C to 80°C (14°F to 176°F)
<b>Physical Characteristics</b>	Color	Black
	Material	Steel
	Product Height	1.1 in [2.7 cm]
	Product Length	2 in [52 mm]
	Product Width	1.7 in [42 mm]
	Weight of Product	2.5 oz [72 g]
<b>Packaging Information</b>	Package Height	2.3 in [58 mm]
	Package Length	6.7 in [17 cm]
	Package Width	4.7 in [12 cm]
	Shipping (Package) Weight	13 oz [368 g]
<b>What's in the Box</b>	Included in Package	1 - SPDIF to RCA converter

1 - universal power adapter (NA, EU, UK, ANZ)

1 - instruction manual

---

Product appearance and specifications are subject to change without notice.