

# Dual-Monitor USB 3.0 Docking Station with HDMI & DVI/VGA

Product ID: USB3SDOCKHDV



This USB 3.0 dock combines three USB 3.0 ports, headphone and microphone audio connectors, and a Gigabit Ethernet RJ45 port, into a single docking station for maximum productivity.

### **Display Adaptability**

Offering flexible dual video combinations right out-of-the-box, this universal laptop docking station features HDMI, DVI and VGA external monitor outputs. Each video output supports HD video resolutions (2048x1152 max) and HD video playback for an ideal solution to expanding your notebook's video capability.

Available display combinations:

- HDMI + VGA
- HDMI + DVI





### **Integrated USB Hub**

The built-in USB hub features three USB 3.0 ports for connecting extra peripherals such as external hard drives or a wired mouse, as if they are connected directly to your laptop.

### **Direct Ethernet Connectivity**

The integrated RJ45 Ethernet port supports speeds of 10/100/1000 Mbps, giving you an instant connection to a wired network.

StarTech.com laptop docking stations can be used for cost savings and faster deployment with just a single cable. This USB 3.0 Docking Station is backed by a competitive 3-year warranty and free lifetime Technical Support.





# Certifications, Reports and Compatibility







### **Applications**

- Shared workspaces
- Hot/Remote desks
- Convert laptop to desktop workstation

#### **Features**

- Connect dual monitors using either HDMI + DVI-D, or HDMI + VGA combinations
- Connect devices with 3 USB 3.0 ports
- Connect to wired networks with the built-in 10/100/1000 Mbps compatible RJ45 Ethernet port
- TAA compliant GSA schedule purchases



## **Data Sheet**

|                                 | Warranty                      | 3 Years   |
|---------------------------------|-------------------------------|---|
| Hardware                        | 4K Support                    | No  |
|                                 | Bus Type                      | USB 3.0   |
|                                 | Chipset ID                    | DisplayLink - DL-3900<br>Genesys Logic - GL3520<br>Realtek - RTL8211E   |
|                                 | Displays Supported            | 2   |
|                                 | Fast-Charge Port(s)           | No  |
|                                 | Industry Standards            | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, USB 3.0  |
| Performance                     | Audio Specifications          | The HDMI port supports audio output   |
|                                 | Auto MDIX                     | Yes   |
|                                 | Compatible Networks           | 10/100/1000 Mbps  |
|                                 | Full Duplex Support           | Yes   |
|                                 | Maximum Analog Resolutions    | 2048x1152 (VGA)   |
|                                 | Maximum Data Transfer Rate    | 5 Gbps (USB 3.0)<br>2 Gbps (Ethernet; Full-Duplex)  |
|                                 | Maximum Digital Resolutions   | 1920x1200 (DVI-D)<br>1920x1080 (HDMI)<br>Lower resolutions are also supported.  |
|                                 | Type and Rate                 | USB 3.0 - 5 Gbit/s  |
| Connector(s)                    | Connector Type(s)             | 1 - DVI-D (25 pin) Female   |
|                                 |                               | 1 - HDMI (19 pin) Female  |
|                                 |                               | 1 - RJ-45 Female  |
|                                 |                               | 1 - USB Type-B (9 pin) USB 3.0 Female   |
|                                 |                               | 1 - VGA (15 pin, High Density D-Sub) Female   |
|                                 |                               | 2 - 3.5 mm Mini-Jack (3 Position) Female  |
|                                 |                               | 3 - USB Type-A (9 pin) USB 3.0 Female   |
| Software                        | OS Compatibility              | Windows® XP SP3 (32-bit), Vista, 7, 8, 8.1, 10 macOS 10.6 - 10.12, 10.14 - 10.15  |
| Special Notes /<br>Requirements | System and Cable Requirements | Available AC electrical outlet  |
|                                 |                               | HDMI (and either DVI-D or VGA if dual display is desired) enabled display device(s) e.g. monitor, projector, HTDV, etc. with cables |
|                                 |                               | USB 3.0 enabled computer system with available USB 3.0 port   |



## **Data Sheet**

| Power                       | Center Tip Polarity          | Positive                                  |
|-----------------------------|------------------------------|---|
|                             | Input Current                | 0.9 A                                     |
|                             | Input Voltage                | 100 - 240 AC                              |
|                             | Output Current               | 4 A                                       |
|                             | Output Voltage               | 5 DC                                      |
|                             | Plug Type                    | В   |
|                             | Power Consumption (In Watts) | 20  |
|                             | Power Source                 | AC Adapter Included                       |
| Environmental               | Humidity                     | 0~90% RH                                  |
|                             | Operating Temperature        | 0°C to 40°C (32°F to 104°F)               |
|                             | Storage Temperature          | -10°C to 60°C (14°F to 140°F)             |
| Physical<br>Characteristics | Cable Length                 | 3 ft [0.9 m]                              |
|                             | Color                        | Black                                     |
|                             | Material                     | Plastic                                   |
|                             | Product Height               | 1.7 in [4.4 cm]                           |
|                             | Product Length               | 12 in [30.4 cm]                           |
|                             | Product Width                | 7 in [17.8 cm]                            |
|                             | Weight of Product            | 10.4 oz [295 g]                           |
| Packaging<br>Information    | Package Height               | 2.6 in [66 mm]                            |
|                             | Package Length               | 11.7 in [29.6 cm]                         |
|                             | Package Width                | 7.7 in [19.5 cm]                          |
|                             | Shipping (Package) Weight    | 31 oz [878 g]                             |
| What's in the Box           | Included in Package          | 1 - Docking Station                       |
|                             |                              | 1 - 0.9m USB 3.0 Cable                    |
|                             |                              | 1 - Universal Power Adapter (NA/EU/UK/AU) |
|                             |                              | 1 - Installation CD                       |
|                             |                              | 1 - Instruction Manual                    |
|                             |                              |   |

Product appearance and specifications are subject to change without notice.