

Redundant 200W Media Converter Chassis Power Supply Module for ETCHS2U

Product ID: ETCHS2UPSU



The ETCHS2UPSU Redundant / Replacement 200W Chassis Power Module for ETCHS2U lets you add a redundant power supply, or keep a replacement power supply on hand for your ETCHS2U media converter chassis.

A hot-swappable, modular design allows a second media converter redundant power supply to be removed or installed while the chassis is still operating, avoiding unnecessary downtime. The power supply is installed using thumbscrews for a quick and easy installation that doesn't require additional tools.


Backed by a StarTech.com 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility







Applications

- Install into the ETCHS2U media converter chassis to provide redundancy
- Store a replacement power supply to have it on hand in the event of a failure

Features

- Redundant / replacement power supply for ETCHS2U
- 200W Output
- Hot-swappable, simple installation
- Active Power Factor Correction (PFC)



Data Sheet

Performance Efficiency Rating 90% (Typical Load) MTBF 65,000 Hours (25°C) Output Power 200W Power Factor Correction Active Power Input Current 2.2A @ 115VAC / 1.2A @ 230VAC Input Voltage 110V-240V AC Output Current 16.6A Output Voltage 12 DC Power Consumption (In Watts) 60 Power Source Standard 120V Power Cords Environmental Humidity 5~90% RH Non-condensing Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Enclosure Type Steel Product Height 4.7 in [12 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Length 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 1.7 Replacement 200W Power Module for ETCHS2U		Warranty	2 Years
MTBF 65,000 Hours (25°C) Output Power 200W 200W Power Factor Correction Active	Performance	Efficiency Rating	90% (Typical Load)
Output Power 200W Power Factor Correction Active Power Input Current 2.2A @ 115VAC / 1.2A @ 230VAC Input Voltage 110V-240V AC Output Voltage 12 DC Power Consumption (In Watts) 60 Power Source Standard 120V Power Cords Environmental Humidity 5~90% RH Non-condensing Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Enclosure Type Steel Product Height 4.7 in [12 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height 2.7 in [69 mm] Package Length 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]			
Power Input Current 2.2A @ 115VAC / 1.2A @ 230VAC Input Voltage 110V-240V AC Output Current 16.6A Output Voltage 12 DC Power Consumption (In Watts) 60 Power Source Standard 120V Power Cords Environmental Humidity 5~90% RH Non-condensing Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height 4.7 in [12 cm] Product Length 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Package Height 14 in [35.6 cm] Package Length Package Width 8.4 in [21.4 cm] Package Width Shipping (Package) Weight 3.9 lb [1.8 kg]		Output Power	
Input Voltage Output Current Output Voltage 12 DC Power Consumption (In Watts) Power Source Operating Temperature Operating Temperat		Power Factor Correction	Active
Output Current Output Voltage 12 DC Power Consumption (In Watts) Power Source Standard 120V Power Cords Environmental Humidity S~90% RH Non-condensing Operating Temperature O°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height 4.7 in [12 cm] Product Length Product Width 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product Veight of Product 2.2 lb [1 kg] Packaging Information Package Height 14 in [35.6 cm] Package Width Shipping (Package) Weight 3.9 lb [1.8 kg]	Power	Input Current	2.2A @ 115VAC / 1.2A @ 230VAC
Output Voltage Power Consumption (In Watts) Power Source Standard 120V Power Cords Finvironmental Humidity Operating Temperature O°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height Product Length Product Width 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height Package Length Package Width Shipping (Package) Weight Standard 120V Power Cords 60 84.7 in [12 cm] 85.6 cm] 86.9 in [22.5 cm] 87.7 in [69 mm] 88.4 in [21.4 cm] 88.4 in [21.4 cm] 88.5 in [21.2 cm] 88.6 cm] 88.6 in [21.8 kg]		Input Voltage	110V-240V AC
Power Consumption (In Watts) Power Source Standard 120V Power Cords Environmental Humidity Operating Temperature Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height Product Length Product Width Weight of Product Weight of Product Packaging Information Package Length Package Width Shipping (Package) Weight Standard 120V Power Cords		Output Current	16.6A
Environmental Humidity Operating Temperature Storage Temperature O°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height Product Length Product Width 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height Package Uidth Package Width Shipping (Package) Weight S-90% RH Non-condensing O°C to 60°C (32°F to 140°F) Steel -10°C to 70°C (14°F to 158°F) Steel -10°C to 70°C (14°F to 158°F) Steel -10°C to 70°C (14°F to 158°F) -10°C to 70°C (14°F to 158°F) Steel -10°C to 70°C (14°F to 158°F)		Output Voltage	12 DC
Environmental Humidity S~90% RH Non-condensing Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height Product Length Product Width 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Length Package Width 8.4 in [35.6 cm] Package Width Shipping (Package) Weight 3.9 lb [1.8 kg]		Power Consumption (In Watts)	60
Operating Temperature 0°C to 60°C (32°F to 140°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Product Height 4.7 in [12 cm] Product Length 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]		Power Source	Standard 120V Power Cords
Physical Characteristics Enclosure Type Product Height Product Length Product Width Weight of Product Packaging Information Package Length Package Width Shipping (Package) Weight Steel Steel 4.7 in [12 cm] 8.3 in [21.2 cm] 8.3 in [21.2 cm] 8.9 in [22.5 cm] 2.2 lb [1 kg] Package Midth Shipping (Package) Weight 14 in [35.6 cm] 8.4 in [21.4 cm] 3.9 lb [1.8 kg]	Environmental	Humidity	5~90% RH Non-condensing
Physical CharacteristicsEnclosure TypeSteelProduct Height4.7 in [12 cm]Product Length8.3 in [21.2 cm]Product Width8.9 in [22.5 cm]Weight of Product2.2 lb [1 kg]Packaging InformationPackage Height2.7 in [69 mm]Package Length14 in [35.6 cm]Package Width8.4 in [21.4 cm]Shipping (Package) Weight3.9 lb [1.8 kg]		Operating Temperature	0°C to 60°C (32°F to 140°F)
Characteristics Product Height 4.7 in [12 cm] Product Length 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]		Storage Temperature	-10°C to 70°C (14°F to 158°F)
Product Length 8.3 in [21.2 cm] Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Length 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]		Enclosure Type	Steel
Product Width 8.9 in [22.5 cm] Weight of Product 2.2 lb [1 kg] Packaging Information Package Height 14 in [35.6 cm] Package Width Package Width Shipping (Package) Weight 3.9 lb [1.8 kg]		Product Height	4.7 in [12 cm]
Packaging InformationPackage Height2.7 in [69 mm]Package Length14 in [35.6 cm]Package Width8.4 in [21.4 cm]Shipping (Package) Weight3.9 lb [1.8 kg]		Product Length	8.3 in [21.2 cm]
Packaging Information Package Height Package Length Package Width Package Width Shipping (Package) Weight 2.7 in [69 mm] 14 in [35.6 cm] 8.4 in [21.4 cm] 3.9 lb [1.8 kg]		Product Width	8.9 in [22.5 cm]
Package Length 14 in [35.6 cm] Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]		Weight of Product	2.2 lb [1 kg]
Package Width 8.4 in [21.4 cm] Shipping (Package) Weight 3.9 lb [1.8 kg]		Package Height	2.7 in [69 mm]
Shipping (Package) Weight 3.9 lb [1.8 kg]		Package Length	14 in [35.6 cm]
		Package Width	8.4 in [21.4 cm]
What's in the Box Included in Package 1 - Replacement 200W Power Module for ETCHS2U		Shipping (Package) Weight	3.9 lb [1.8 kg]
- '	What's in the Box	Included in Package	1 - Replacement 200W Power Module for ETCHS2U

Product appearance and specifications are subject to change without notice.