

# 1-Port Gigabit Midspan - PoE+ Injector - 802.3at and 802.3af

Product ID: POEINJ1G



This Gigabit Power over Ethernet (PoE+) injector supplies power and data connectivity to a Gigabit PoE-compliant device using standard Ethernet cable, at distances of up to 100 m (330 ft.).

The PoE midspan is a cost-effective alternative to upgrading your existing network switch to a PoE-capable model.

## Convenience and cost savings

This versatile PoE injector lets you connect a PoE-powered device (PD) to a non-PoE network switch, so you can avoid the expense and aggravation of replacing your existing switch with a PoE-enabled model. It supplies up to 30 watts of power, so you can easily power and access a high-power PoE-compliant device, such as an IP camera or a wireless access point (WAP), using traditional copper (RJ45) Ethernet cable. The midspan injector makes it easy to extend data and power connectivity to your PoE+ device across long distances, even in a remote location where a typical power outlet isn't available.

## Easy to set up in mixed environments

You can integrate this compact injector discreetly into a variety of environments. It features a surface-mountable housing that's perfect for installing on walls or under a desk, but it's also palm-sized, for use on desktop surfaces.

Plus, with plug-and-play operation, you can enjoy fast and hassle-free setup without disrupting your workflow.

## Intelligent power allocation

Not sure which class your PoE device is? The Gigabit PoE+ injector automatically detects the power requirements of your connected PoE PD, and delivers the appropriate level of power without damaging your device.

The POEINJ1G is backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Ideal for high-power PoE+ devices requiring Gigabit speeds such as PTZ (Pan, Tilt, Zoom) cameras and Wi-Fi® access points (WAP)
- Enable remote installation of touchscreens, information kiosks, and phones in locations where a power connection isn't available
- Perfect for small and home offices, as well as SMB applications, including system integrations, and IT administration

### Features

- Easily connect, power, and operate a Gigabit PoE-powered device (PD)
- Supplies up to 30-watts power output
- Flexible setup, with a desktop-sized, or surface-mountable housing
- Save money by using your existing Cat5 or better Ethernet cable
- Fast, plug-and-play setup and operation, with no configuration required
- Provides one PoE+ (PSE, power and data) 10/100/1000Mbps compliant RJ45 port - 802.3at and 802.3af
- Integrates shielded RJ45 connectors
- Automatically detects the powered device to provide the appropriate level of power output

<b>Hardware</b>	Warranty	2 Years
	Industry Standards	IEEE 802.3af PoE, IEEE 802.3at PoE+  IEEE 802.3 (10BASE-T), IEEE 802.3u (100BASE-TX), IEEE 802.3ab (1000BASE-T)
	Ports	1
<b>Performance</b>	Maximum Cable Length	328 ft [100 m]
	Maximum Data Transfer Rate	2 Gbps (Full-Duplex)
	Power Output	48 V DC, 30 W
<b>Connector(s)</b>	Connector Type(s)	2 - RJ-45 Female
<b>Special Notes / Requirements</b>	Patents and Licenses	The following patents are licensed for this product. This list might not be all inclusive. <ul style="list-style-type: none"> <li>• United States Patent No. 5,406,260 (expired)</li> <li>• United States Patent No. 6,650,622</li> <li>• United States Patent No. 7,457,250</li> <li>• United States Patent No. 8,155,012</li> <li>• United States Patent No. 8,902,760</li> <li>• United States Patent No. 8,942,107</li> <li>• United States Patent No. 9,019,838</li> <li>• United States Patent No. 9,049,019</li> <li>• United States Patent Application No. 14/695,456</li> <li>• United States Patent Application No. 14/726,940</li> </ul>
	System and Cable Requirements	If your connected devices do not meet the IEEE 802.3af or IEEE 802.3at PoE standard, then the POEINJ1G will not inject power to the connected device(s) / Ethernet cable(s)
<b>Indicators</b>	LED Indicators	1 - Power
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.75 A
	Input Voltage	100 - 240 AC
	Output Current	0.64 A
	Output Voltage	56 DC
	Plug Type	M
	Power Consumption (In Watts)	36
Power Source	AC Adapter Included	
<b>Environmental</b>	Humidity	10~90% RH (Non-Condensing)
	Operating Temperature	0°C to 45°C (32°F to 113°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)

<b>Physical Characteristics</b>	Color	Black
	Material	Plastic
	Product Height	1 in [2.5 cm]
	Product Length	2.8 in [70 mm]
	Product Width	2.5 in [63 mm]
	Weight of Product	1.8 oz [50 g]
<b>Packaging Information</b>	Package Height	2.4 in [61 mm]
	Package Length	6 in [15.2 cm]
	Package Width	8.1 in [20.5 cm]
	Shipping (Package) Weight	18 oz [511 g]
<b>What's in the Box</b>	Included in Package	1 - POE+ Injector
		4 - Mounting Screws
		1 - Power Adapter
		4 - Power Cords (NA/UK/EU/ANZ)
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.