

# Composite and S-Video to HDMI Converter with Audio

Product ID: VID2HDCON



The VID2HDCON Composite and S-Video to HDMI® Video Converter (with Audio) lets you connect an S-Video or Composite device, along with supporting 3.5mm audio, to your HDMI monitor or television.

Equipped with convenient selector switches for easy configuration, the S-Video/Composite to HDMI converter is able to function with both NTSC and PAL systems, and offers support for output resolutions up to 1600x1200 (PC) or 1080p (TV) to seamlessly integrate with almost any display.

The converter features an integrated 3.5mm audio connection that enables sending the output through a single HDMI cable to your destination display, avoiding the hassle of running a separate audio cable.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Convert VCRs, DVD players, camcorders, video game consoles and other home theater devices to work on HDMI displays

### Features

- Functions with NTSC and PAL systems
- PC/TV resolution selector switch for compatibility with many different displays
- 50/60 Hz frame rate conversion
- On Screen Display
- Plug and play installation - no software/drivers required
- Advance 3D motion adaptive de-interlace
- 3D (frame based) motion adaptive YNR/CNR noise reduction

<b>Hardware</b>	Warranty	2 Years
	Active or Passive Adapter	Active
	Audio	Yes
	AV Input	3.5 mm Stereo Audio
		Composite
		S-Video
AV Output	HDMI	
Industry Standards	NTSC 3.58 and PAL	
<b>Performance</b>	Supported Resolutions	PC - 1600x1200, 1280x1024, 1024x768 TV - 1080p, 720p, 576p, 480p
<b>Connector(s)</b>	Connector Type(s)	1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - Composite Video (1 x RCA) Female Input 1 - HDMI (19 pin) Female Output 1 - S-Video (4 pin, Mini-DIN) Female Input
<b>Indicators</b>	LED Indicators	1 - Red - S-Video, Yellow - Composite Video
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.3A
	Input Voltage	100 - 240 AC
	Output Current	1.2A
	Output Voltage	5 DC
	Plug Type	M
	Power Consumption (In Watts)	2.5
	Power Source	AC Adapter Included
<b>Environmental</b>	Humidity	20~90% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
<b>Physical Characteristics</b>	Color	Black
	Enclosure Type	Plastic
	Product Height	1.3 in [3.4 cm]
	Product Length	6.5 in [16.4 cm]
	Product Width	6.4 in [16.3 cm]

	Weight of Product	2.8 oz [79 g]
<b>Packaging Information</b>	Package Height	2.2 in [56 mm]
	Package Length	4.9 in [12.4 cm]
	Package Width	6.1 in [15.5 cm]
	Shipping (Package) Weight	10.9 oz [310 g]
<b>What's in the Box</b>	Included in Package	1 - Composite/S-Video to HDMI Converter
		1 - Universal Power Adapter (NA/JP, EU, UK, ANZ)
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.