

VGA to HDMI Adapter with USB Audio & Power – Portable VGA to HDMI Converter – 1080p

Product ID: VGA2HDU



The VGA2HDU VGA to HDMI adapter lets you turn the VGA port on your Desktop or Laptop computer into an HDMI output port.

With the VGA2HDU, you can expand your VGA video output to accommodate the increasing number of displays and projectors that only support HDMI.

Not all VGA converters are created equal. This adapter ensures you're harnessing the highest video quality from your VGA output, with support for resolutions up to 1920x1080 (1080p).

For hassle-free setup the VGA to HDMI adapter allows for plug-and-play installation. Plus, with a built-in USB power cable the device is powered using the USB port on your computer. The VGA to HDMI adapter will work with any computer operating system, but when working with a Windows® computer the adapter supports native USB audio, allowing you to add your computer audio to the HDMI signal.

The VGA2HDU is backed by a StarTech.com 2-year warranty and free lifetime technical support.

www.startech.com 1 800 265 1844



Data Sheet

Certifications, Reports and Compatibility





C€ F©



Applications

- Connect your VGA-equipped computer to an HDMI home theatre system
- Share video content from your VGA-equipped computer on an HDMI television or projector
- Connect a legacy VGA-equipped device to a newer HDMI display
- Share audio from your Windows based PC

Features

- Supports video resolutions up to 1920x1080
- Plug-and-play installation
- USB powered
- USB audio
- Compact, lightweight design

StarTechcom

Hard-to-find made easy*

Data Sheet

Hardware Active or Passive Adapter Active Adapter Style Adapters Adapter Style Adapters Audio Ves AV Input VGA AV Output HDMI Cabling HDMI Chipset ID Micro Silicon - MS9282 Performance Maximum Analog Resolutions 1920x1080 Maximum Digital Resolutions 1920x1080 (1080p) 1680x1050 (1080p) 1680x1050 (1080p) 1680x2000 1680x200 (1080p) 1680x2000 (1080p) 1680x200 (1080p) 1680x200 (1080p) 1680x200 (1080p)		Warranty	2 Years
Adapter Style Adapters Auloi Yes AV Input VGA AV Output HDMI Cabling HDMI Chipset ID Micro Silicon - MS9282 Performance Maximum Analog Resolutions 1920x1080 Marimum Digital Resolutions 1920x1080 MTF Jo63,669 hours Supported Resolutions 1660x1000 MONICOS (MSKGA+) 1600x1000 1600x1000 1400x1050 (MSKGA+) 1600x2000 1400x1050 (MSKGA+) 1600x2000 1400x1050 (MSKGA+) 1600x4000 1400x1050 (MSKGA+) 1200x600 1200x600 1200x768 (MSGA) 1200x768 1200x768 (MSGA) 1200x768 1200x769 (MSGA) 1200x768 1		-	
Audio Yes AV Input VGA AV Output HDMI Cabling HDMI Chipset ID Micro Silicon - MS9282 Performance Maximum Analog Resolutions 1920x1080 Maximum Digital Resolutions 1920x1080 MTBF 1,063,669 hours Supported Resolutions 1920x1080 (1080p) 1660x1050 (WSXGA+) 1660x1050 (WSXGA+) 1560x500 1440x9900 140x9900 1400x9900 140x9900 1400x900 140x9900 1400x1050 (WSGA) 1560x400 1580x400 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p) 1280x720p (720p)	Hardware		
AV InputVGAAV OutputHDHICablingHDHIChipset IDMicro Silicor - MS9282PerformanceMaximum Analog Resolutions920x1080Maximum Digital Resolutions1920x1080MTBF.063,669 hoursSupported Resolutions1920x1080 (1080p)1660x1050 (WSXGA+)1660x1050 (WSXGA+)1660x2001400x2001400x2001400x2001400x2001560x7801360x7681360x7681360x7681360x7681360x7691280x700 (720p)1280x720 (720p)1280x7681280x720 (720p)1280x768200metor FSConnector FTonnector FSConnector BFeeluirementsNteFeeluirementsNteFeeluirementsConnector BConnector FSNteFielui Notes CmNteFeeluirementsNteFeeluirementsNteFielui Notes CmNteFielui Notes CmNte <td< th=""><th></th><th>Adapter Style</th><th>Adapters</th></td<>		Adapter Style	Adapters
AV Output HDMI Cabling HDMI Chipset ID Micro Silicon - MS9282 Performance Maximum Analog Resolutions 1920x1080 Maximum Digital Resolutions 1920x1080 1920x1080 MTBF 1,063,669 hours 1680x1050 (WSXGA+) Supported Resolutions 1920x1080 (1080p) 1680x1050 (WSXGA+) 1600x1200 1680x1050 (WSXGA+) 1600x1200 1600x1200 1680x1050 (WSXGA+) 1366x768 1260x1200 1260x900 1440x900 1440x900 1440x900 1440x900 1440x900 1260x768 1260x768 1260x01260 1280x600 1280x768 1260x01260 1280x768 (WXGA) 1280x768 (WXGA) 1280x768 (WSGA) 1280x768 (WSGA) 1280x768 (WSGA) 1280x7200 (720p) 1280x768 (WSGA) 1280x768 (WSGA)		Audio	Yes
Cabling HDMI Chipset ID Micro Silicon - MS9282 Performance Maximum Analog Resolutions 1920x1080 Maximum Digital Resolutions 1920x1080 1080 MTBF 1,063,669 hours 1680x1050 (WSXGA+) Supported Resolutions 1920x1080 (1080p) 1680x1050 (WSXGA+) 1600x1200 1600x900 1440x900 1440x900 1440x900 1440x900 1400x900 1440x900 1440x900 1400x900 1440x900 180x768 1200x1080 (1080p) 1600x1200 180x050 (SXGA+) 1360x768 180x01050 (SXGA+) 1360x768 1200x000 120x000 120x000 1200x000 120x050 (SXGA+) 1360x768 1200x000 120x050 (SXGA+) 1360x768 1200x000 120x000 120x000 1200x000		AV Input	VGA
Chipset IDMicro Silicon - MS9282PerformanceMaximum Analog Resolutions1920x1080Maximum Digital Resolutions1920x1080Supported Resolutions1920x1080 (1080p)1660x1505 (WSSGA+)1660x1505 (WSSGA+)1660x12001600x12001600x12001440x900140x9001440x900140x900140x900140x900140x900140x900140x900140x900140x900140x9001280x6001280x6001280x8001280x788 (WSGA)1280x9601280x780 (YC20)1280x6001280x780 (WSGA)1280x7801280x780 (WSGA)1280x7801280x780 (WSGA)1280x7801280x780 (WSGA)1280x7801280x780 (WSGA)1280x7801280x780 (MSGA)1280x7801280x780 (MSGA)1280x780<		AV Output	HDMI
Performance Maximum Analog Resolutions 1920x1080 Maximum Digital Resolutions 1920x1080 MTBF 1,063,669 hours Supported Resolutions 1920x1080 (1080p) 1660x1505 (WSXGA+) 1660x1505 (WSXGA+) 1600x1200 1600x1200 1600x1200 1400x1055 (SXGA+) 1366x768 1360x768 1280x960 1280x960 1280x960 1280x960 1280x720 (720p) 1280x768 1280x500 (SVGA) 1280x720 Wide Screen Supported Yes Connector S Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male 1 - USB Type-A (4 pin) USB 2.0 Male Special Notes / Mote Supports native USB audio. Frequirements Wide Screen Supported Ves used with a Computer, volume levels cannot be adjusted using the operating system. Volume levels cannot be adjusted using the operating system. Volume levels cannot be adjusted by the output device (TV, speakers, audio receiver, etc).		Cabling	HDMI
Maximum Digital Resolutions1920x1080MTBF1,063,669 hoursSupported Resolutions1920x1080 (1080p) 1600x1200 1600x900 1400x1050 (WSXGA+) 1366x768 1280x1024 1280x800 1280x768 (WXGA) 1280x768 (WXGA) <th></th> <th>Chipset ID</th> <th>Micro Silicon - MS9282</th>		Chipset ID	Micro Silicon - MS9282
MTBF1,063,669 hoursSupported Resolutions920x1080 (1080p) 1680x1050 (WSXGA+) 1600x900 1440x900 	Performance	Maximum Analog Resolutions	1920×1080
Supported Resolutions 1920x1080 (1080p) 1680x1050 (WSXGA+) 1600x1200 1600x300 1440x900 1440x900 1440x900 1440x900 1400x1050 (SXGA+) 1366x768 1280x768 1280x768 1280x768 1280x768 (WXGA) 1280x768		Maximum Digital Resolutions	1920x1080
I680x1050 (WSXGA+) I660x1200 I600x1200 I600x1200 I600x1200 I600x1200 I400x1050 (SXGA+) I366x768 I360x768 I280x960		MTBF	1,063,669 hours
1600x12001600x9001400x9001400x1050 (SXGA+)1366x7681360x7681360x7681280x10241280x9601280x768 (WXGA)1280x768 (WXGA)128		Supported Resolutions	
1600x900 1440x900 1400x1050 (SXGA+) 1366x768 1360x768 1280x1024 1280x800 1280x720p (720p) 1280x600 1280x720p (720p) 1280x600 1280x768 (WXGA) 1280x720p (720p) 1280x600 1152x864 1024x768 800x600 (SVGA) 640x480 (480p)Connector (s)Connector AConnector F1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 MaleSpecial Notes / RequirementsNoteMote RequirementsVen used with a Windows@ computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels cannot be adjusted using the operati			
Initial server serve			
1400x1050 (SXGA+) 1366x768 1360x708 1280x200 1280x200 1280x708 (WXGA) 1280x708 (WXGA) 1280x709 (720p) 1280x600 1152x864 1024x768 800x600 (SVGA) 640x480 (480p) Wide Screen Supported Yes Connector (s) Connector A Connector B 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
1366×768 1360×768 1360×768 1280×1024 1280×1024 1280×200 1280×200 1280×200 1280×768 (WXGA) 1280×700 (720p) 1280×768 (WXGA) 1280×768 (WXGA) 1280×768 (WXGA) 1280×768 (WXGA) 1280×768 (WXGA) 1280×700 (720p) 1280×768 (WXGA) 1280×768 (WXGA) 1280×768 (WXGA) 1280×700 (720p) 1280×700 (720p) 1280×700 (720p) 1280×768 (WXGA) 1024×768 (WXGA) <th></th> <th></th> <th></th>			
1360x768 1280x1024 1280x960 1280x768 (WXGA) 1280x720p (720p) 1280x768 (WXGA) 1280x720p (720p) 1280x768 (WXGA) 1280x720p (720p) 1280x768 (WXGA) 1024x768 800x600 (SVGA) 640x480 (480p)Connector (s)Wide Screen SupportedYesConnector A1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 MaleSpecial Notes / RequirementsNoteWhen used with a Windows® computer this adapter supports native USB audio.If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
1280x9601280x768 (WXGA)1280x768 (WXGA)1280x720p (720p)1280x700 (720p)1280x60152x8641024x768800x600 (SVGA)640x480 (480p)Wide Screen SupportedYesConnector(s)Connector A1 - VGA (15 pin, High Density D-Sub) Male Input1 - USB Type-A (4 pin) USB 2.0 MaleConnector B1 - HDMI (19 pin) Female OutputSpecial Notes / RequirementsNoteVien used with a Windows@ computer this adapter supports native USB audio.If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels cannot be.			
1280x800 1280x768 (WXGA) 1280x720p (720p) 1280x600 1152x864 1024x768 800x600 (SVGA) 640x480 (480p)Wide Screen SupportedYesConnector(s)Connector AConnector B1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male 1 - HDMI (19 pin) Female OutputSpecial Notes / RequirementsNote Hamper A (4 pin) USB 2.0 Male 1 - HDMI (19 pin) Female OutputSpecial Notes / RequirementsNote Hamper A (4 pin) USB 2.0 Male 1 - HDMI (19 pin) Female OutputSpecial Notes / RequirementsNote Hamper A (4 pin) USB 2.0 Male 1 - HDMI (19 pin) Female Output			1280x1024
1280x768 (WXGA) 1280x720p (720p) 1280x600 1152x864 1024x768 Wide Screen Supported Yes Connector(s) Connector B Connector B 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Wide Screen Supported Ves			1280x960
1280x720p (720p) 1280x600 1152x864 1024x768 800x600 (SVGA) 640x480 (480p) Wide Screen Supported Yes Connector(s) Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male 1 - USB Type-A (4 pin) USB 2.0 Male Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc). If used with a computer, volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
1280x600 1152x864 1024x768 800x600 (SVGA) 640x480 (480p) Yes Connector(s) Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male 1 - USB Type-A (4 pin) USB 2.0 Male Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
1152x864 1024x768 800x600 (SVGA) 640x480 (480p)Wide Screen SupportedYesConnector(s)Connector A1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 MaleSpecial Notes / RequirementsNoteWhen used with a Windows® computer this adapter supports native USB audio.If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
1024x768 800x600 (SVGA) 800x600 (SVGA) 640x480 (480p) Wide Screen Supported Yes Connector(s) Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male 1 - USB Type-A (4 pin) USB 2.0 Male Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
Sobx 600 (SVGA) 640x480 (480p) Wide Screen Supported Yes Connector(s) Connector A I - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male Connector B I - HDMI (19 pin) Female Output Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
Wide Screen Supported Yes Connector(s) Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
Wide Screen Supported Yes Connector(s) Connector A 1 - VGA (15 pin, High Density D-Sub) Male Input 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			
I - USB Type-A (4 pin) USB 2.0 Male I - HDMI (19 pin) Female Output Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).		Wide Screen Supported	
Connector B 1 - HDMI (19 pin) Female Output Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).	Connector(s)	Connector A	1 - VGA (15 pin, High Density D-Sub) Male Input
Special Notes / Requirements Note When used with a Windows® computer this adapter supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).			1 - USB Type-A (4 pin) USB 2.0 Male
Requirements supports native USB audio. If used with a computer, volume levels cannot be adjusted using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).		Connector B	1 - HDMI (19 pin) Female Output
using the operating system. Volume levels can be controlled by the output device (TV, speakers, audio receiver, etc).	-	Note	
Power Power Source USB-Powered			using the operating system. Volume levels can be controlled
	Power	Power Source	USB-Powered

www.startech.com 1 800 265 1844

StarTechcom

Hard-to-find made easy*

Data Sheet

Environmental	Humidity	40%-85%RH
	Operating Temperature	0°C to 60°C (32°F to 140°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
Physical Characteristics	Color	Black
	Material	Plastic
	Product Height	0.6 in [1.5 cm]
	Product Length	10.2 in [26 cm]
	Product Width	1.4 in [35 mm]
	Weight of Product	2.5 oz [70.7 g]
Packaging Information	Package Height	1.2 in [30 mm]
	Package Length	6.8 in [17.3 cm]
	Package Width	5.7 in [14.4 cm]
	Shipping (Package) Weight	5.3 oz [151 g]
What's in the Box	Included in Package	1 - VGA to HDMI adapter w/ USB power & audio
		1 - 2ft USB Extension Cable

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844