

## 3.5in Drive Bay IDE to Single CF SSD Adapter Card Reader

Product ID: 35BAYCF2IDE



This Compact Flash IDE adapter is a perfect solution for accessing CompactFlash (CF I, CF II) and IBM Micro Drive media, allowing you to access the flash/micro drive media as if it were an IDE hard drive.

The CF/IDE adapter can be installed in the computer case through simple mounting in an available 3.5in drive bay, for connection to the computer IDE bus through either a 40 or 44-pin connection.

Designed and constructed to provide a reliable media card platform, the CF IDE adapter is backed by StarTech.com's 2-year warranty.

### Certifications, Reports and Compatibility



### Applications

- Use your compact flash card as a bootable and removable device
- Excellent for swapping operating systems quickly without having to take your computer apart.
- Connect your compact flash card to a 40 or 44 pin IDE slot

### Features

- Quick and driver free installation into any IDE 40 pin and 44 pin slot
- Fully compatible with Compact Flash Type I/II and IBM Micro-drive
- Allows Compact flash card to be used as bootable storage
- Easy to use jumpers offer simple master/slave drive setting
- Can be mounted in the front or rear panel of your case, to fit into any 3.5" bay or available expansion slot
- Easily swap cards in and out with built-in push button ejector

	Warranty	2 Years
<b>Hardware</b>	Interface	IDE
<b>Performance</b>	Maximum Data Transfer Rate	133 MBps
	Memory Media Type	CF (Compact Flash I/II Card)
<b>Connector(s)</b>	Drive Connectors	1 - CompactFlash (50 pin) Slot
	Host Connectors	1 - IDE (40 Pin, EIDE/PATA) Male 1 - SP4 (4 pin, Small Drive Power) Male
<b>Software</b>	OS Compatibility	OS independent; No software or drivers required
<b>Special Notes / Requirements</b>	<b>Note</b>	This product does not support hot-swapping of flash cards while the PC is powered on. You must turn-off your computer to switch cards.
<b>Environmental</b>	Humidity	5% ~ 85% RH
	Operating Temperature	-55°C to 85°C (-67°F to 185°F)
	Storage Temperature	-55°C to 85°C (-67°F to 185°F)
<b>Physical Characteristics</b>	Product Height	1 in [25 mm]
	Product Length	3.8 in [97 mm]
	Product Width	3.9 in [10 cm]
	Weight of Product	4.6 oz [129 g]
<b>Packaging Information</b>	Package Height	6.2 in [15.8 cm]
	Package Length	8.7 in [22 cm]
	Package Width	1.9 in [48 mm]
	Shipping (Package) Weight	7.6 oz [215 g]
<b>What's in the Box</b>	Included in Package	1 - Compact Flash to IDE Adapter 1 - 3.5" Enclosure 1 - Full Profile Expansion Slot Bracket 1 - SP4 to LP4 Molex Power Cable 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.