

# USB-C Dual-4K Monitor Docking Station for Laptops - 60W USB Power Delivery - SD Card Reader

Product ID: DK30CHDDPPD



This dual-monitor USB-C<sup>™</sup> dock transforms your MacBook or Windows® laptop into a dual Ultra HD 4K workstation, with support for 4K DisplayPort and HDMI monitors. It gives you all the connections to create a fully capable workstation, including an SD<sup>™</sup> card reader slot.

The USB-C docking station features USB Power Delivery 2.0 (60W), to power and charge your laptop as you work. It's the perfect companion for your MacBook Pro or other Thunderbolt<sup>TM</sup> 3 equipped laptop.

### Create a dual-4K video workstation

The USB-C dock expands the display capabilities of your laptop across two Ultra HD 4K monitors. It enables DisplayLink® and USB-C DP Alt Mode to allow dual 4K video output to HDMI and DisplayPort 4K monitors. With the dual-4K dock, you can connect:

- 1x 4K DisplayPort display at 3840 x 2160 resolution @ 30Hz
- 1x 4K HDMI display at 3840 x 2160 resolution @ 30Hz





#### SD card reader

The dock provides direct access to your SD memory cards or microSD $^{\text{TM}}$  cards (with adapter). The SD card slot can also be used for additional storage and backup through macOS X Time Machine or Windows 10 File History.

### **Ample connections**

The dock provides four USB 3.0 (Type-A) ports to connect your peripherals, including a USB 3.0 fast-charge and sync port, a Gigabit Ethernet port, and a combined 3.5 mm audio and microphone port.

### **Universal support**

Compatible with Mac and Windows, this universal dock works with USB-C and Thunderbolt 3 enabled laptops.

# Connected Device Transparency with the StarTech.com MAC Address Changer Utility

the DK30CHDDPPD, includes a free Windows® application that enables you to better manage your enterprise network security. When you connect to your network through the ethernet port of the DK30CHHPD, the computer's MAC address is typically not broadcast to the network, as your network only sees the MAC address of the docking station. However, the StarTech.com MAC Address Changer or Cloning software enables the USB-C dock to use MAC address spoofing of the connected Windows laptop rather than the MAC address of the dock itself. This ensures your network administrators have full visibility of each device on the network and can monitor and limit activity accordingly. To request access to our MAC Address Changer utility, please contact our Technical Support Department by phone, live chat, or email <a href="mailto:support@startech.com">support@startech.com</a>

The DK30CHDDPPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.





## Certifications, Reports and Compatibility











### **Applications**

- Ideal for professionals who work with highly detailed graphics or data-intensive applications, including graphic and web designers, videographers, animators, analysts and engineers (CAD)
- Scale your desktop across multiple displays perfect for government, finance, marketing and sales environments
- Expand the connectivity of your laptop compatible with MacBook
  Pro, Dell XPS 15 or other USB-C enabled laptops

#### **Features**

- Turn your USB-C equipped laptop into a dual Ultra HD 4K workstation by connecting two external 4K monitors: 1x DisplayPort (DisplayLink) 4K @ 30Hz and 1x HDMI (DP Alt Mode) 4K @ 30Hz
- Universal USB-C dock supports macOS and Windows
- Powers and charges your laptop, with 60W USB Power Delivery 2.0
- SD and microSD (with adapter) memory card reader supports SD 4.0 and UHS-II (backward compatible with older SD card versions)
- Connect your peripheral devices, with four USB 3.0 ports
- Quickly charge your phone or tablet with the always-on USB 3.0 fastcharge and sync port
- Thunderbolt 3 port compatible
- Gigabit Ethernet port adds wired network connectivity to your workstation
- Convenient On/Off button on front of docking station



### **Data Sheet**

Warranty 3 Years Hardware 4K Support Yes USB-C Bus Type Chipset ID DisplayLink - DL-5700 Genesys Logic - GL3215 VIA Labs - VL813 Texas Instruments - TPS65983 Displays Supported 2 Fast-Charge Port(s) Yes **Industry Standards** USB Power Delivery Specification Rev. 2.0 USB Battery Charging Specification Rev. 1.2 DisplayPort 1.2 IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1 Interface **USB 3.0 Performance** Auto MDIX Yes Compatible Networks 10/100/1000 Mbps Full Duplex Support Yes **General Specifications** Supports SD 4.0 and UHS-II (Ultra High Speed) for high speed file transfers, with bus speed up to 312MB/s Maximum Data Transfer Rate 5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex) Maximum Digital Resolutions HDMI (DP Alt Mode) - 3840 x 2160p @30Hz DisplayPort (DisplayLink) - 3840 x 2160p @30Hz Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p. Memory Media Type SD/MMC (Secure Digital/Multimedia Card) SDHC (Secure Digital High Capacity) SDXC (Secure Digital eXtended Capacity) microSD (Micro Secure Digital) (adapter required) microSDHC (Micro Secure Digital High Capacity) (adapter required) microSDXC (Micro Secure Digital eXtended Capacity) (adapter required) Type and Rate USB 3.0 - 5 Gbit/s



### **Data Sheet**

	LIACD Cups	Vec
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - DisplayPort (20 pin) Female
		1 - HDMI (19 pin) Female
		1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Female
		1 - USB 3.0 A (Fast-Charge, 9 pin) Female
		3 - USB Type-A (9 pin) USB 3.0 Female
		1 - RJ-45 Female
		1 - 3.5 mm Mini-Jack (4 Position) Female
		1 - SD / MMC Slot Female
Software	OS Compatibility	Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 - 10.15 Chrome OS™ v55+
Special Notes / Requirements	Note	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.
		4K resolution is supported on both video ports. A 4K-capable DisplayPort or HDMI display is required to achieve 4Kx2K resolutions
		USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps
		The card reader supports popular SD cards (SDSC, SDHC and SDXC including UHS cards), and is backwards compatible with older SD card versions. The card reader will also support microSD $^{\text{TM}}$ and miniSD $^{\text{TM}}$ (with adapter) and MMCmobile $^{\text{TM}}$ , RS-MMC $^{\text{TM}}$ and MMCplus $^{\text{TM}}$ (with adapter).
	System and Cable Requirements	USB-C enabled computer with an available USB Type-C port
Power	Center Tip Polarity	Positive
	Input Current	2 A
	Input Voltage	100 - 240 AC
	Output Current	5 A
	Output Voltage	20V DC
	Power Delivery	60W
	Power Source	AC Adapter Included
Environmental	Humidity	
	Operating Temperature	0°C to 60°C (32°F to 140°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
	•	•



### **Data Sheet**

Physical Characteristics	Cable Length	39.4 in [1000 mm]
	Color	Black & Silver
	Material	Plastic
	Product Height	1 in [2.5 cm]
	Product Length	8.7 in [22 cm]
	Product Width	3.1 in [80 mm]
	Weight of Product	9.2 oz [261 g]
Packaging Information	Package Height	3.5 in [90 mm]
	Package Length	10.6 in [27 cm]
	Package Width	6.1 in [15.5 cm]
	Shipping (Package) Weight	2.9 lb [1.3 kg]
What's in the Box	Included in Package	1 - docking station
		1 - USB-C cable
		1 - universal power adapter (NA/JP, ANZ)
		1 - instruction manual

Product appearance and specifications are subject to change without notice.