

# 4 Port VGA Over CAT5 Video Extender - 450ft (150m)

Product ID: ST1214T



The ST1214T 4 Port VGA Video Extender over Cat 5 allows a single VGA source to be broadcast to up to four remote displays at distances of up to 500 feet (150 meters). Designed for use with our ST121 VGA Video over Cat 5 extension series of devices, the ST1214T is one of many options designed to help you create a custom VGA distribution and extension solution for many applications including digital signage and video conferencing.

Consisting of the transmitter unit only, this product requires a single <u>ST121R</u> receiver unit per remote display that you are connecting. If you are looking for an eight port transmitter solution, we offer our <u>ST1218T</u> 8 port VGA extender unit.

For even more versatility, the <u>ST121EXT</u> VGA over Cat 5 Repeater can be used to increase the total VGA extension distance by an additional 500 feet(150 meters), allowing the original VGA signal to be broadcast a total distance of 1000 feet (300 meters) from transmitter to receiver. Similarly, up to three repeater units can be used between the transmitter and receiver units allowing a monitor to be connected at each repeater station , while further extending the total distance between the transmitter and receiver units.

www.startech.com 1 800 265 1844



#### **Data Sheet**

This product is TAA compliant and backed by a Startech.com 2-year warranty with free lifetime technical support.

www.startech.com 1 800 265 1844




#### **Data Sheet**

**Certifications, Reports** and Compatibility







www.startech.com 1 800 265 1844



Hard-to-find made easy\*

### **Data Sheet**

		2.4
	Warranty	2 Years
Hardware	Audio	No
	Cabling	Cat 5 UTP or better
	Daisy-Chain	Yes
	Ports	4
Performance	Max Distance	150 m / 500 ft
	Maximum Analog Resolutions	1600x1200 @ 150ft(50m) 1280x1024 @ 300ft(100m) 1024x768 @ 500ft(150m)
Connector(s)	Local Unit Connectors	1 - VGA (15 pin, High Density D-Sub) Male
		2 - VGA (15 pin, High Density D-Sub) Female
		4 - RJ-45 Female
Special Notes / Requirements	System and Cable Requirements	One <u>ST121R</u> receiver unit per remote display that you are connecting
Power	Center Tip Polarity	Positive
	Input Voltage	100 - 240 AC
	Output Current	0.6A
	Output Voltage	12 DC
	Power Consumption (In Watts)	7.2
	Power Source	AC Adapter Included
Physical Characteristics	Color	Black
	Enclosure Type	Aluminum
	Product Height	0.8 in [2.1 cm]
	Product Length	4.1 in [10.3 cm]
	Product Width	2.5 in [63.9 mm]
	Weight of Product	7.1 oz [201 g]
Packaging Information	Package Height	3.9 in [98 mm]
	Package Length	4 in [10.1 cm]
	Package Width	8.7 in [22 cm]
	Shipping (Package) Weight	18.7 oz [529 g]
What's in the Box	Included in Package	1 - VGA Extender - Transmitter

www.startech.com 1 800 265 1844



## **Data Sheet**

- 4 Rubber Feet
- 1 Universal Power Adapter (NA/UK/EU)

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844