

# HDMI to VGA Video Adapter Converter with Audio - HD to VGA Monitor 1080p

Product ID: HDMI2VGA



The HDMI2VGA HDMI® to VGA converter converts digital HDMI or DVI video signals to analog VGA, taking the input resolution from your device and converting it into an analog signal at the same resolution.

The converter also separates the audio stream from the HDMI signal (HDMI LPCM 2-Channel) and converts it to analog stereo audio that can be used with the VGA display.

With support for resolutions of up to 1080p, the HDMI2VGA converter is a perfect solution for connecting video cards (desktop or laptop) or consumer electronics devices such as game consoles or home theater receivers that offer an HDMI output to a VGA display.

The HDMI2VGA adapter/converter is simple to use, with no complicated settings, and is backed by a 2-year warranty and free, lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Convert an HDMI® signal from a Blu-Ray player, PS3, or other HDMI-enabled source to work with an analog VGA display
- Convert a DVI or HDMI signal from a desktop or notebook video card to work with an analog VGA display / projector

### Features

- Supports VGA and Component (YPbPr) output conversion
- Compliant with HDCP 1.1, and DVI
- Built-in EDID
- Audio video are separated on output

<b>Hardware</b>	Warranty	2 Years
	Active or Passive Adapter	Active
	Audio	Yes
	AV Input	HDMI
	AV Output	3.5 mm Stereo Audio VGA Component
<b>Performance</b>	Audio Specifications	HDMI® LPCM 2-channel Input
	Supported Resolutions	PC: 1920x1200, 1600x1200, 1680x1050, 1440x900, 1280x1024, 1280x800, 1152x864, 1024x768, 800x600, 640x480  HD: 1080p/1080i (50, 60Hz), 720p (50, 60Hz), 576i/576p (50Hz), 480i/480p (60Hz)
<b>Connector(s)</b>	Connector A	1 - HDMI (19 pin) Female Input
	Connector B	1 - 3.5 mm Mini-Jack (3 Position) Female Output 1 - VGA (15 pin, High Density D-Sub) Female Output
<b>Special Notes / Requirements</b>	<b>Note</b>	PC resolutions below 1280x1024 may support multiple refresh rates; 60Hz supported across all  Audio from computers running macOS is not supported  When using the VGA to component breakout cable, maximum resolution is 720i
<b>Indicators</b>	LED Indicators	1 - Power (Red)
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.3A
	Input Voltage	100 - 240 AC
	Output Current	1.2A
	Output Voltage	5 DC
	Plug Type	N
	Power Consumption (In Watts)	6
	Power Source	AC Adapter Included
<b>Environmental</b>	Humidity	0~60% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-10°C to 60°C (14°F to 140°F)

<b>Physical Characteristics</b>	Color	Black
	Product Height	3.6 in [9.2 cm]
	Product Length	3 in [76 mm]
	Product Width	3 in [76 mm]
	Weight of Product	6.4 oz [181 g]
<b>Packaging Information</b>	Package Height	2.4 in [60 mm]
	Package Length	4.6 in [11.8 cm]
	Package Width	8.3 in [21 cm]
	Shipping (Package) Weight	18.9 oz [536 g]
<b>What's in the Box</b>	Included in Package	1 - HDMI to VGA Converter w/ Audio
		1 - VGA to Component Breakout Cable
		1 - Universal Power Adapter (US/UK/EU/AUS)
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.