




## EMT SET SCREW CONNECTORS

Uninsulated Set Screw Connector, Steel

B03



Catalog #: 2008

### APPLICATIONS

For use in dry locations to bond EMT conduit to a box or enclosure. RACO steel set screw connectors provide concrete-tight connections when taped.

### PRODUCT FEATURES

- All steel construction insures mechanical protection for the raceway
- Tri-head screws may be installed using a slotted, Phillips, or Robertson head screwdriver
- 2-1/2 in. to 4 in. trade sizes are also UL listed for use on Rigid/IMC conduit, allowing for design and installation flexibility
- All components are zinc electroplated for corrosion protection
- 1/2 in. to 1 in. trade sizes have one set screw, 1-1/4 in. to 4 in. trade sizes have two set screws
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

### UL LISTED

2-1/2" - 4" Standard 514B, File E195969, E195970

### CULUS

1/2" - 2" Standard 514B, C22.2 # 18

### COMPLIANCES

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings\\_January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings_January_2015.pdf)

### GENERAL PRODUCT INFORMATION

Sub Class:	Uninsulated
Trade Size:	2"

### DRAWING DIMENSIONS

Dimension A:	2.425"
Dimension B:	2.235"
Dimension D:	.408"
Dimension E:	1/4 - 28

### PACKAGING

Package Type:	Carton
Ship Carton Qty.:	20
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	55.3
Ship Carton Length (in.):	12.88
Ship Carton Width (in.):	8.75
Ship Carton Height (in.):	5.63
Pallet Qty:	1800
UPC Number:	050169020081