



# 40W Compact USB-C Wall Charger - GaN Technology, USB-C Power Delivery 3.0

# MODEL NUMBER: U280-W01-40C1











Travel-sized USB-C charger provides up to 40W to quickly and efficiently charge your notebook or laptop at home or on the move.

#### **Features**

#### 40W USB Type-C Charger Gets Your Mobile Device Ready in a Hurry, Wherever You Are

This single-port USB charger lets you quickly and safely charge your USB-C mobile device. Plug it into any NEMA 1-15R, NEMA 5-15R or NEMA 5-15/20R AC outlet to ensure your MacBook Pro, Chromebook, Windows laptop, smartphone, tablet or other USB-C device charges at its fastest possible speed. The USB-C port supports USB Power Delivery (PD) 3.0 charging up to 5V 3A (15W), 9V 3A (27W), 15V 2.6A (39W) and 20V 2A (40W).

#### Gallium Nitride Technology Allows High-Wattage Capacity in a Compact Package

This USB wall charger is smaller and lighter than most standard wall chargers that come with a laptop, measuring less than 3.5 cubic inches. Ideal for travel, it is designed using GaN technology, which has a higher power density than silicon and provides higher efficiency than standard USB-C fast chargers. It also operates under much cooler temperatures, despite its small size, meaning it won't get hot while charging your device.

#### Built-In Auto-Sensing Adjusts to Proper Power Level to Get Your Device to 100%

The USB-C port features auto-sensing technology that automatically adjusts to your device's appropriate power level, perfect for fast-charging tablets and e-readers. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your device's batteries are at full capacity.

## Folding Plug Design Perfectly Sized for Travel

The compact USB Type-C charger, small enough to fit in the palm of your hand, is easy to carry in your purse, suitcase, backpack or laptop bag. The NEMA 1-15P plug folds into the unit when not in use to shield it from damage and prevent it from snagging or scratching your bag's contents.

#### **Highlights**

- Ideal for charging smartphones, tablets, e-readers and laptops while traveling
- USB-C PD 3.0 port supports a maximum power capacity of 40W for fast charging
- Gallium nitride (GaN) technology generates less heat to support high-efficiency charging
- Connects to any NEMA 1-15R,
   5-15R or 5-15R/20R AC outlet for immediate charging
- Measures less than 3.5 cu. in., making it perfectly sized for convenient travel use

#### **Applications**

 Charge a smartphone, tablet, laptop or other USB-C mobile device without taking up a valuable USB port on your computer

## **Package Includes**

 U280-W01-40C1 USB-C Wall Charger, GaN, USB-C PD 3.0, 40W

# **Specifications**

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332249050 |



| Over Current Protection     | Υ                                                                          |  |
|-----------------------------|----------------------------------------------------------------------------|--|
|                             |                                                                            |  |
| OUTPUT                      |                                                                            |  |
| Charging Ports / Amps       | 1.5A                                                                       |  |
| Output Capacity             | 5V 3A (15W), 9V 3A (27W), 15V 2.6A (39W) and 20V 2A (40W)                  |  |
| Charging Method             | USB                                                                        |  |
| INPUT                       |                                                                            |  |
| Input Connection Type       | NEMA 1-15P                                                                 |  |
| Voltage Compatibility (VAC) | 100; 110; 110-240; 120; 125; 127; 200; 200-240; 208; 208/240; 220; 220-240 |  |
| Input Frequency             | 50/60 Hz                                                                   |  |
| Input Current               | 100-240V, 1.5A (MAX)                                                       |  |
| Product Length (in.)        | 1.476                                                                      |  |
| Product Length (cm.)        | 3.75                                                                       |  |
| Product Length (ft.)        | 0.123                                                                      |  |
| Product Length (m.)         | 0.0375                                                                     |  |
| BATTERY                     |                                                                            |  |
| Battery Charging (1.2 Port) | Yes                                                                        |  |
| PHYSICAL                    |                                                                            |  |
| Color                       | White                                                                      |  |
| Material of Construction    | PC945                                                                      |  |
| Unit Dimensions (hwd / cm)  | 3.75 x 3.65 x 4.02                                                         |  |
| Unit Dimensions (hwd / in.) | 1.476 x 1.437 x 1.583                                                      |  |
| Unit Packaging Type         | Вох                                                                        |  |
| Unit Weight (kg)            | 0.07                                                                       |  |
| Unit Weight (lbs.)          | 0.146                                                                      |  |
| ENVIRONMENTAL               |                                                                            |  |
| Operating Temperature Range | 0 to 25 C (32 to 77 F)                                                     |  |
| Storage Temperature Range   | -20 to 85 C (-4 to 185 F)                                                  |  |
| Power Consumption (Watts)   | 40W                                                                        |  |
| Operating Humidity Range    | 20 to 90 %, RH Non-Condensing                                              |  |
| Storage Humidity Range      | 5 to 95 %, RH Non-Condensing                                               |  |
| CONNECTIONS                 |                                                                            |  |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| Ports                               | 1                                     |  |
|-------------------------------------|---------------------------------------|--|
| Side A - Connector 1                | NEMA 1-15P (NON-POLARIZED)            |  |
| Side B - Connector 1                | USB Type-C (FEMALE)                   |  |
| FEATURES & SPECIFICATIONS           |                                       |  |
| Driver Required                     | No                                    |  |
| Quick Charge Compliant              | 3.0                                   |  |
| Technology                          | USB 3.0 (SuperSpeed); USB 3.1 (Gen 1) |  |
| CERTIFICATIONS                      |                                       |  |
| Certifications                      | UL, FCC                               |  |
| WARRANTY                            |                                       |  |
| Product Warranty Period (Worldwide) | 2-year limited warranty               |  |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>