


EBC012



Wiring block

ZDO8H05HMSS0000-00STAK190MSS



Application	
System	Free from silicone; gold-plated contacts
Free from silicone	yes
Electrical data	
Operating voltage [V]	10...30 DC; (cULus - Class 2 source required)
Max. current load per module/slot [A]	4
Max. current load total [A]	10
Outputs	
Electrical design	PNP

EBC012



Wiring block

ZDO8H05HMSS0000-00STAK190MSS

Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67; ((enclosure type 1))
Mechanical data		
Weight	[g]	306
Dimensions	[mm]	33 x 60 x 152
Material		PA
Number of ports splitter box		8
Connector type		M12
Displays / operating elements		
Display	Switching status	16 x LED, yellow
	Power	1 x LED, green
Accessories		
Accessories (supplied)		Protective caps: 2 labels: 8
Remarks		
Pack quantity		1 pcs.
Electrical connection - Connection		
Connector: 1 x M23; Moulded body: PA; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm		


EBC012



Wiring block

ZDO8H05HMSS0000-00STAK190MSS

Connection



EBC012



Wiring block

ZDO8H05HMSS0000-00STAK190MSS

Electrical connection - slot

Connector: 8 x M12; Moulded body: PA; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm

