





Specifications



Key Characteristics




Catalog Page # 	142
Product Number	149050
UPC	754473587802
UOM	Each
Brand Name	Brady®
Country of Origin 	Germany
HTS Code (Harmonized Tariff Schedule) 	8443.32.1050
ECCN (Export Commodity Control Number) 	EAR99

Dimensions




Dimensions	11.4 in H x 9.9 in W x 18.1 in D
Height	11.4 in
Width	9.9 in
Depth	18.1 in
Display Size	4.3 in (diagonal)
Weight	22.05 lb

Product Features


Applications 	Barcode Labeling, Circuit Board Labeling, Component and Equipment Labeling, Data and Telecommunications Labeling, Electrical Labeling, Inventory and Inspection Labeling, Laboratory Labeling, Wire and Cable Labeling
Connectivity Options 	Ethernet, RS232, USB 2.0, USB Host

Display Type	Color Touch Screen
Media Sensor Type	Black Mark, Gap Sensor, Notch, Reflective Sensor
Memory	256 MB RAM;SD Flash Memory Card Reader
Mode of Operation 	PC Connect
Plug Type	IEC Type B
Power Supply Voltage	100 to 240 V @ 50 to 60 Hz
Ribbon Ink Wind Direction 	Side In/Side Out
Supply Remaining Gauge 	No

Printing Specifications

Automatic Label Set Up 	No
Barcode Capability	Yes
Barcode Symbologies - 2D	Aztec, Codablock F, Data Matrix, GS1 Data Bar, Micro PDF 417, PDF 417, QR Code, RSS 14, RSS 14 Truncated, UPS MaxiCode
Barcode Symbologies - Linear	Codabar;Code 128 Subsets A,B,C;Code 39;Code 93;EAN 8,13;EAN/UPC Appendix 2;EAN/UPC Extension 5;FIM;HIBC;Interleaved 2 of 5 Code 39;JAN 8,13;MSI;Plessey;PostNet;RSS 14;UPC A,E,E0
Calibration Required? 	Yes
Color Printing Capability	Single Color
Maximum Labels per Day 	7 000
Maximum Print Speed	11.8 in/s
Print Resolution	300 dpi
Print Technology	Direct Thermal, Thermal Transfer
Media Sensor Adjustment	Yes

Compatibility

Label Material Types	Flame Retardant Wire Wrap;Metalized Polyester Tape;Nomex;Nylon Cloth;Paper;Polyester;Polyethylene;Polyimide;Polyolefin;Polypropylene;Push Button and Raised Panel Labels;Self-Laminating Vinyl;Tags;Tamper-Evident Metallized Polyester;Vinyl
Continuous & Die-Cut Materials Supported	Continuous Tapes & Die-Cut Labels
Custom Media Parts Available	Yes
Maximum Label/Tape Width	4.33 in
Maximum Print Width	4.16 in
Minimum Label Length 	0.125 in
Minimum Liner Width	0.36 in
Maximum Liner Width	4.49 in
Software Compatibility	Brady® Workstation, Labelmark™ Software, Windows Based Driver for Third Party Software Use
Languages Available	Bulgarian, Chinese (Simplified), Croatian, Czech, Danish, Dutch, English (US), Farsi, Finnish, French (France), German, Greek, Hungarian, Italian, Korean, Lithuanian, Macedonian, Norwegian, Polish, Portuguese (Portugal), Romanian, Russian, Serbian, Slovenian, Spanish (Spain), Swedish, Turkish

What's Included

Includes	(1) Brady Workstation Product and Wire ID Software Suite (BWS-PWID-EM), (1) BradyPrinter i7100 300 dpi Printer (149050), (1) Configuration Settings Manual, (1) Owners Manual, (1) Product CD with Driver, (1) U.S. Type B Plug Power Cord, (1) USB Cable, (2) 1 In Ribbon Takeup Cores
Warranty	5 Years

Compliance

--	--

UNSPSC 

45101519

California Prop 65 

 WARNING: Cancer - www.p65warnings.ca.gov