

Resi-Gard® Flexible Raceway

Ideal for providing a main chase from the main distribution panel to a secondary hub in the attic or basement, Resi-Gard nonmetallic flexible raceway is available in 3/4" to 2" diameter sizes with factory installed pull tape in sizes 1" to 2".

The raceway is hand bendable, lightweight and easily cut to length to reduce scrap. Bright orange color clearly signifies a low voltage installation.

- Listed as a General Purpose Raceway



Standard Length Coils

Size	Pull Tape	Part No.	Reel Length	Prod. Wt. (lbs.) Reel
3/4"	Empty*	SCE4X1-100	100	11.5
1"	900 lbs.	SCF4X1C-100	100	17.9
1 1/4"	900 lbs.	SCG4X1C-100	100	21.5
1 1/2"	900 lbs.	SCH4X1C-50	50	11.2
2"	900 lbs.	SCJ4X1C-100	50	13.4

*If installing own tape, a lubricated polyester is recommended.

Standard Length Reels*

Size	Pull Tape	Part No.	Reel Length	Prod. Wt. (lbs.) Reel
3/4"	Empty	SCE4X1-1000	1000	115.0
1"	900 lbs.	SCF4X1C-1500	1500	268.5
2"	900 lbs.	SCJ4X1C-500	500	133.5

* Made to order

Resi-Gard® Fittings



Quick Connect Coupling

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCA240E	3/4"	25	.783
SCA240F	1"	20	.972



Quick Connect Threaded Adapter

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCA243E	3/4"	25	.633
SCA243F	1"	20	.778



Quick Connect Snap-In Adapter

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCA253E	3/4"	25	.783
SCA253F	1"	20	.918



Except where noted by ▶



Male Terminal Adapter*

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCE943G	1 1/4"	50	3
SCE943H	1 1/2"	25	2.5
SCE943J	2"	50	6.8



Standard Couplings*

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
SCE940G	1 1/4"	30	3.5
SCE940H	1 1/2"	25	3.9
SCE940J	2"	30	5.2

* Must be cemented to Resi-Gard® Flexible Raceway using ONLY Resi-Gard Solvent Cement



PVC Lock Nut



Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
▶ LT9LE	3/4"	700	4
▶ LT9LF	1"	600	4