



| REV | DESCRIPTION | DATE | APP |
|------------------|-----------------|------------|-----|
| 0 | INITIAL RELEASE | 11/19/2018 | DD |
| REVISION HISTORY | | | |

| | | |
|--|-----------------------|------------------|
| EI SENSOR TECHNOLOGIES www.ei-sensor.com © COPYRIGHT | NTC THERMISTOR | |
| | DRAWN BY: DAN DANKERT | |
| P/N ED3518J202- | SCALE: NONE | LAYER: 0 OF 2 |
| | REV: 0 | DATE: 11/19/2018 |

This PROPRIETARY document is the property of EI Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand.

RESISTANCE @ +25°C = 2,000 Ω ± 5%
 RESISTANCE/TEMPERATURE CURVE = "18"
 BETA "β" (0 TO +50°C) = 3,417°K NOMINAL
 TEMPERATURE COEFFICIENT @ +25°C = -3.85%/°C NOMINAL
 DISSIPATION CONSTANT = 2 mW/°C NOMINAL (AIR)
 THERMAL TIME CONSTANT = 10 SECONDS NOMINAL (AIR)
 MAXIMUM TEMPERATURE RATING = +300°C

ROHS COMPLIANT

PACKAGING: SEE TABLE

| PART NUMBER | PACKAGING |
|--------------|-----------------------------|
| ED3518J202-B | BULK |
| ED3518J202-T | TAPE & REEL PER IEC 60286-1 |

El Sensor Technologies

Resistance Versus Temperature Table

P/N ED3518J202 Revision "0"

Resistance @ +25°C = 2,000 Ω

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C/R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|----------------------------------|------------------------|
| -55 | -67.0 | 54.120 | 108,240 |
| -54 | -65.2 | 50.760 | 101,521 |
| -53 | -63.4 | 47.631 | 95,262 |
| -52 | -61.6 | 44.715 | 89,430 |
| -51 | -59.8 | 41.996 | 83,992 |
| -50 | -58.0 | 39.460 | 78,920 |
| -49 | -56.2 | 37.093 | 74,186 |
| -48 | -54.4 | 34.884 | 69,767 |
| -47 | -52.6 | 32.820 | 65,639 |
| -46 | -50.8 | 30.891 | 61,782 |
| -45 | -49.0 | 29.088 | 58,176 |
| -44 | -47.2 | 27.401 | 54,803 |
| -43 | -45.4 | 25.823 | 51,646 |
| -42 | -43.6 | 24.346 | 48,692 |
| -41 | -41.8 | 22.962 | 45,925 |
| -40 | -40.0 | 21.666 | 43,332 |
| -39 | -38.2 | 20.451 | 40,902 |
| -38 | -36.4 | 19.312 | 38,623 |
| -37 | -34.6 | 18.243 | 36,486 |
| -36 | -32.8 | 17.240 | 34,479 |
| -35 | -31.0 | 16.298 | 32,596 |
| -34 | -29.2 | 15.414 | 30,827 |
| -33 | -27.4 | 14.582 | 29,165 |
| -32 | -25.6 | 13.801 | 27,603 |
| -31 | -23.8 | 13.067 | 26,133 |
| -30 | -22.0 | 12.376 | 24,751 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|---------------------|---------------------|---------------------------------------|---------------------------|
| -29 | -20.2 | 11.725 | 23,451 |
| -28 | -18.4 | 11.113 | 22,227 |
| -27 | -16.6 | 10.537 | 21,074 |
| -26 | -14.8 | 9.9937 | 19,987 |
| -25 | -13.0 | 9.4818 | 18,964 |
| -24 | -11.2 | 8.9992 | 17,998 |
| -23 | -9.4 | 8.5441 | 17,088 |
| -22 | -7.6 | 8.1147 | 16,229 |
| -21 | -5.8 | 7.7095 | 15,419 |
| -20 | -4.0 | 7.3269 | 14,654 |
| -19 | -2.2 | 6.9655 | 13,931 |
| -18 | -0.4 | 6.6241 | 13,248 |
| -17 | 1.4 | 6.3015 | 12,603 |
| -16 | 3.2 | 5.9965 | 11,993 |
| -15 | 5.0 | 5.7080 | 11,416 |
| -14 | 6.8 | 5.4351 | 10,870 |
| -13 | 8.6 | 5.1768 | 10,354 |
| -12 | 10.4 | 4.9324 | 9,864.8 |
| -11 | 12.2 | 4.7008 | 9,401.6 |
| -10 | 14.0 | 4.4815 | 8,963.0 |
| -9 | 15.8 | 4.2737 | 8,547.4 |
| -8 | 17.6 | 4.0768 | 8,153.6 |
| -7 | 19.4 | 3.8900 | 7,780.0 |
| -6 | 21.2 | 3.7129 | 7,425.8 |
| -5 | 23.0 | 3.5449 | 7,089.8 |
| -4 | 24.8 | 3.3854 | 6,770.8 |
| -3 | 26.6 | 3.2340 | 6,468.0 |
| -2 | 28.4 | 3.0903 | 6,180.6 |
| -1 | 30.2 | 2.9537 | 5,907.4 |
| 0 | 32.0 | 2.8240 | 5,648.0 |
| 1 | 33.8 | 2.7008 | 5,401.6 |
| 2 | 35.6 | 2.5836 | 5,167.3 |
| 3 | 37.4 | 2.4723 | 4,944.5 |
| 4 | 39.2 | 2.3663 | 4,732.6 |
| 5 | 41.0 | 2.2655 | 4,531.1 |
| 6 | 42.8 | 2.1696 | 4,339.2 |
| 7 | 44.6 | 2.0783 | 4,156.6 |
| 8 | 46.4 | 1.9913 | 3,982.6 |
| 9 | 48.2 | 1.9085 | 3,817.0 |
| 10 | 50.0 | 1.8296 | 3,659.2 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+ 25°C) | Resistance (Ω Nominal) |
|---------------------|---------------------|--|---------------------------|
| 11 | 51.8 | 1.7544 | 3,508.8 |
| 12 | 53.6 | 1.6827 | 3,365.4 |
| 13 | 55.4 | 1.6143 | 3,228.7 |
| 14 | 57.2 | 1.5491 | 3,098.3 |
| 15 | 59.0 | 1.4869 | 2,973.9 |
| 16 | 60.8 | 1.4276 | 2,855.2 |
| 17 | 62.6 | 1.3709 | 2,741.9 |
| 18 | 64.4 | 1.3168 | 2,633.7 |
| 19 | 66.2 | 1.2652 | 2,530.4 |
| 20 | 68.0 | 1.2158 | 2,431.7 |
| 21 | 69.8 | 1.1687 | 2,337.4 |
| 22 | 71.6 | 1.1236 | 2,247.3 |
| 23 | 73.4 | 1.0806 | 2,161.1 |
| 24 | 75.2 | 1.0394 | 2,078.8 |
| 25 | 77.0 | 1.0000 | 2,000.0 |
| 26 | 78.8 | 0.96232 | 1,924.6 |
| 27 | 80.6 | 0.92627 | 1,852.5 |
| 28 | 82.4 | 0.89176 | 1,783.5 |
| 29 | 84.2 | 0.85873 | 1,717.5 |
| 30 | 86.0 | 0.82710 | 1,654.2 |
| 31 | 87.8 | 0.79680 | 1,593.6 |
| 32 | 89.6 | 0.76778 | 1,535.6 |
| 33 | 91.4 | 0.73997 | 1,479.9 |
| 34 | 93.2 | 0.71332 | 1,426.6 |
| 35 | 95.0 | 0.68778 | 1,375.6 |
| 36 | 96.8 | 0.66328 | 1,326.6 |
| 37 | 98.6 | 0.63979 | 1,279.6 |
| 38 | 100.4 | 0.61726 | 1,234.5 |
| 39 | 102.2 | 0.59564 | 1,191.3 |
| 40 | 104.0 | 0.57489 | 1,149.8 |
| 41 | 105.8 | 0.55497 | 1,109.9 |
| 42 | 107.6 | 0.53585 | 1,071.7 |
| 43 | 109.4 | 0.51749 | 1,035.0 |
| 44 | 111.2 | 0.49986 | 999.71 |
| 45 | 113.0 | 0.48292 | 965.83 |
| 46 | 114.8 | 0.46664 | 933.28 |
| 47 | 116.6 | 0.45100 | 901.99 |
| 48 | 118.4 | 0.43596 | 871.92 |
| 49 | 120.2 | 0.42150 | 843.00 |
| 50 | 122.0 | 0.40760 | 815.20 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|------------------------------------|------------------------|
| 51 | 123.8 | 0.39423 | 788.46 |
| 52 | 125.6 | 0.38137 | 762.73 |
| 53 | 127.4 | 0.36899 | 737.98 |
| 54 | 129.2 | 0.35708 | 714.15 |
| 55 | 131.0 | 0.34561 | 691.22 |
| 56 | 132.8 | 0.33457 | 669.14 |
| 57 | 134.6 | 0.32394 | 647.89 |
| 58 | 136.4 | 0.31371 | 627.41 |
| 59 | 138.2 | 0.30385 | 607.69 |
| 60 | 140.0 | 0.29434 | 588.69 |
| 61 | 141.8 | 0.28519 | 570.38 |
| 62 | 143.6 | 0.27637 | 552.73 |
| 63 | 145.4 | 0.26786 | 535.72 |
| 64 | 147.2 | 0.25966 | 519.31 |
| 65 | 149.0 | 0.25175 | 503.50 |
| 66 | 150.8 | 0.24412 | 488.24 |
| 67 | 152.6 | 0.23676 | 473.52 |
| 68 | 154.4 | 0.22966 | 459.32 |
| 69 | 156.2 | 0.22281 | 445.62 |
| 70 | 158.0 | 0.21620 | 432.40 |
| 71 | 159.8 | 0.20982 | 419.63 |
| 72 | 161.6 | 0.20365 | 407.30 |
| 73 | 163.4 | 0.19770 | 395.40 |
| 74 | 165.2 | 0.19195 | 383.90 |
| 75 | 167.0 | 0.18640 | 372.80 |
| 76 | 168.8 | 0.18100 | 362.00 |
| 77 | 170.6 | 0.17579 | 351.58 |
| 78 | 172.4 | 0.17076 | 341.52 |
| 79 | 174.2 | 0.16590 | 331.80 |
| 80 | 176.0 | 0.16120 | 322.41 |
| 81 | 177.8 | 0.15667 | 313.33 |
| 82 | 179.6 | 0.15228 | 304.56 |
| 83 | 181.4 | 0.14804 | 296.09 |
| 84 | 183.2 | 0.14395 | 287.89 |
| 85 | 185.0 | 0.13998 | 279.97 |
| 86 | 186.8 | 0.13615 | 272.30 |
| 87 | 188.6 | 0.13244 | 264.89 |
| 88 | 190.4 | 0.12886 | 257.71 |
| 89 | 192.2 | 0.12539 | 250.77 |
| 90 | 194.0 | 0.12203 | 244.05 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|---------------------|---------------------|---------------------------------------|---------------------------|
| 91 | 195.8 | 0.11877 | 237.55 |
| 92 | 197.6 | 0.11563 | 231.25 |
| 93 | 199.4 | 0.11258 | 225.15 |
| 94 | 201.2 | 0.10962 | 219.25 |
| 95 | 203.0 | 0.10676 | 213.52 |
| 96 | 204.8 | 0.10399 | 207.98 |
| 97 | 206.6 | 0.10130 | 202.61 |
| 98 | 208.4 | 0.098700 | 197.40 |
| 99 | 210.2 | 0.096177 | 192.35 |
| 100 | 212.0 | 0.093730 | 187.46 |
| 101 | 213.8 | 0.091358 | 182.72 |
| 102 | 215.6 | 0.089057 | 178.11 |
| 103 | 217.4 | 0.086825 | 173.65 |
| 104 | 219.2 | 0.084660 | 169.32 |
| 105 | 221.0 | 0.082560 | 165.12 |
| 106 | 222.8 | 0.080521 | 161.04 |
| 107 | 224.6 | 0.078543 | 157.09 |
| 108 | 226.4 | 0.076622 | 153.24 |
| 109 | 228.2 | 0.074758 | 149.52 |
| 110 | 230.0 | 0.072948 | 145.90 |
| 111 | 231.8 | 0.071190 | 142.38 |
| 112 | 233.6 | 0.069482 | 138.96 |
| 113 | 235.4 | 0.067824 | 135.65 |
| 114 | 237.2 | 0.066213 | 132.43 |
| 115 | 239.0 | 0.064647 | 129.29 |
| 116 | 240.8 | 0.063126 | 126.25 |
| 117 | 242.6 | 0.061647 | 123.29 |
| 118 | 244.4 | 0.060210 | 120.42 |
| 119 | 246.2 | 0.058812 | 117.62 |
| 120 | 248.0 | 0.057454 | 114.91 |
| 121 | 249.8 | 0.056133 | 112.27 |
| 122 | 251.6 | 0.054848 | 109.70 |
| 123 | 253.4 | 0.053598 | 107.20 |
| 124 | 255.2 | 0.052383 | 104.77 |
| 125 | 257.0 | 0.051200 | 102.40 |
| 126 | 258.8 | 0.050049 | 100.10 |
| 127 | 260.6 | 0.048929 | 97.858 |
| 128 | 262.4 | 0.047839 | 95.678 |
| 129 | 264.2 | 0.046778 | 93.556 |
| 130 | 266.0 | 0.045746 | 91.492 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|------------------------------------|------------------------|
| 131 | 267.8 | 0.044740 | 89.480 |
| 132 | 269.6 | 0.043761 | 87.522 |
| 133 | 271.4 | 0.042808 | 85.616 |
| 134 | 273.2 | 0.041879 | 83.758 |
| 135 | 275.0 | 0.040975 | 81.950 |
| 136 | 276.8 | 0.040093 | 80.186 |
| 137 | 278.6 | 0.039235 | 78.470 |
| 138 | 280.4 | 0.038399 | 76.798 |
| 139 | 282.2 | 0.037583 | 75.166 |
| 140 | 284.0 | 0.036789 | 73.578 |
| 141 | 285.8 | 0.036015 | 72.030 |
| 142 | 287.6 | 0.035260 | 70.520 |
| 143 | 289.4 | 0.034524 | 69.048 |
| 144 | 291.2 | 0.033807 | 67.614 |
| 145 | 293.0 | 0.033107 | 66.214 |
| 146 | 294.8 | 0.032425 | 64.850 |
| 147 | 296.6 | 0.031760 | 63.520 |
| 148 | 298.4 | 0.031111 | 62.222 |
| 149 | 300.2 | 0.030478 | 60.956 |
| 150 | 302.0 | 0.029860 | 59.720 |
| 151 | 303.8 | 0.029223 | 58.446 |
| 152 | 305.6 | 0.028641 | 57.282 |
| 153 | 307.4 | 0.028072 | 56.144 |
| 154 | 309.2 | 0.027516 | 55.032 |
| 155 | 311.0 | 0.026974 | 53.948 |
| 156 | 312.8 | 0.026444 | 52.888 |
| 157 | 314.6 | 0.025926 | 51.852 |
| 158 | 316.4 | 0.025421 | 50.842 |
| 159 | 318.2 | 0.024927 | 49.854 |
| 160 | 320.0 | 0.024445 | 48.890 |
| 161 | 321.8 | 0.023973 | 47.946 |
| 162 | 323.6 | 0.023513 | 47.026 |
| 163 | 325.4 | 0.023063 | 46.126 |
| 164 | 327.2 | 0.022624 | 45.248 |
| 165 | 329.0 | 0.022194 | 44.388 |
| 166 | 330.8 | 0.021775 | 43.550 |
| 167 | 332.6 | 0.021364 | 42.728 |
| 168 | 334.4 | 0.020964 | 41.928 |
| 169 | 336.2 | 0.020572 | 41.144 |
| 170 | 338.0 | 0.020189 | 40.378 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|------------------------------------|------------------------|
| 171 | 339.8 | 0.019815 | 39.630 |
| 172 | 341.6 | 0.019449 | 38.898 |
| 173 | 343.4 | 0.019091 | 38.182 |
| 174 | 345.2 | 0.018742 | 37.484 |
| 175 | 347.0 | 0.018400 | 36.800 |
| 176 | 348.8 | 0.018066 | 36.132 |
| 177 | 350.6 | 0.017739 | 35.478 |
| 178 | 352.4 | 0.017419 | 34.838 |
| 179 | 354.2 | 0.017107 | 34.214 |
| 180 | 356.0 | 0.016801 | 33.602 |
| 181 | 357.8 | 0.016502 | 33.004 |
| 182 | 359.6 | 0.016210 | 32.420 |
| 183 | 361.4 | 0.015924 | 31.848 |
| 184 | 363.2 | 0.015644 | 31.288 |
| 185 | 365.0 | 0.015370 | 30.740 |
| 186 | 366.8 | 0.015103 | 30.206 |
| 187 | 368.6 | 0.014840 | 29.680 |
| 188 | 370.4 | 0.014584 | 29.168 |
| 189 | 372.2 | 0.014333 | 28.666 |
| 190 | 374.0 | 0.014088 | 28.176 |
| 191 | 375.8 | 0.013847 | 27.694 |
| 192 | 377.6 | 0.013612 | 27.224 |
| 193 | 379.4 | 0.013382 | 26.764 |
| 194 | 381.2 | 0.013156 | 26.312 |
| 195 | 383.0 | 0.012936 | 25.872 |
| 196 | 384.8 | 0.012720 | 25.440 |
| 197 | 386.6 | 0.012508 | 25.016 |
| 198 | 388.4 | 0.012301 | 24.602 |
| 199 | 390.2 | 0.012099 | 24.198 |
| 200 | 392.0 | 0.011900 | 23.800 |
| 201 | 393.8 | 0.011706 | 23.412 |
| 202 | 395.6 | 0.011515 | 23.030 |
| 203 | 397.4 | 0.011329 | 22.658 |
| 204 | 399.2 | 0.011146 | 22.292 |
| 205 | 401.0 | 0.010967 | 21.934 |
| 206 | 402.8 | 0.010792 | 21.584 |
| 207 | 404.6 | 0.010620 | 21.240 |
| 208 | 406.4 | 0.010451 | 20.902 |
| 209 | 408.2 | 0.010286 | 20.572 |
| 210 | 410.0 | 0.010125 | 20.250 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|------------------------------------|------------------------|
| 211 | 411.8 | 0.009966 | 19.932 |
| 212 | 413.6 | 0.009811 | 19.622 |
| 213 | 415.4 | 0.009659 | 19.318 |
| 214 | 417.2 | 0.009510 | 19.020 |
| 215 | 419.0 | 0.009364 | 18.728 |
| 216 | 420.8 | 0.009220 | 18.440 |
| 217 | 422.6 | 0.009080 | 18.160 |
| 218 | 424.4 | 0.008942 | 17.884 |
| 219 | 426.2 | 0.008807 | 17.614 |
| 220 | 428.0 | 0.008675 | 17.350 |
| 221 | 429.8 | 0.008545 | 17.090 |
| 222 | 431.6 | 0.008418 | 16.836 |
| 223 | 433.4 | 0.008293 | 16.586 |
| 224 | 435.2 | 0.008170 | 16.340 |
| 225 | 437.0 | 0.008050 | 16.100 |
| 226 | 438.8 | 0.007922 | 15.844 |
| 227 | 440.6 | 0.007807 | 15.614 |
| 228 | 442.4 | 0.007693 | 15.386 |
| 229 | 444.2 | 0.007582 | 15.164 |
| 230 | 446.0 | 0.007472 | 14.944 |
| 231 | 447.8 | 0.007365 | 14.730 |
| 232 | 449.6 | 0.007259 | 14.518 |
| 233 | 451.4 | 0.007155 | 14.310 |
| 234 | 453.2 | 0.007053 | 14.106 |
| 235 | 455.0 | 0.006953 | 13.906 |
| 236 | 456.8 | 0.006854 | 13.708 |
| 237 | 458.6 | 0.006758 | 13.516 |
| 238 | 460.4 | 0.006663 | 13.326 |
| 239 | 462.2 | 0.006569 | 13.138 |
| 240 | 464.0 | 0.006477 | 12.954 |
| 241 | 465.8 | 0.006387 | 12.774 |
| 242 | 467.6 | 0.006299 | 12.598 |
| 243 | 469.4 | 0.006211 | 12.422 |
| 244 | 471.2 | 0.006126 | 12.252 |
| 245 | 473.0 | 0.006042 | 12.084 |
| 246 | 474.8 | 0.005959 | 11.918 |
| 247 | 476.6 | 0.005878 | 11.756 |
| 248 | 478.4 | 0.005798 | 11.596 |
| 249 | 480.2 | 0.005719 | 11.438 |
| 250 | 482.0 | 0.005642 | 11.284 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+ 25°C) | Resistance (Ω Nominal) |
|------------------|------------------|-------------------------------------|------------------------|
| 251 | 483.8 | 0.005566 | 11.132 |
| 252 | 485.6 | 0.005492 | 10.984 |
| 253 | 487.4 | 0.005418 | 10.836 |
| 254 | 489.2 | 0.005346 | 10.692 |
| 255 | 491.0 | 0.005275 | 10.550 |
| 256 | 492.8 | 0.005206 | 10.412 |
| 257 | 494.6 | 0.005137 | 10.274 |
| 258 | 496.4 | 0.005070 | 10.140 |
| 259 | 498.2 | 0.005003 | 10.006 |
| 260 | 500.0 | 0.004938 | 9.876 |
| 261 | 501.8 | 0.004874 | 9.748 |
| 262 | 503.6 | 0.004811 | 9.622 |
| 263 | 505.4 | 0.004749 | 9.498 |
| 264 | 507.2 | 0.004689 | 9.378 |
| 265 | 509.0 | 0.004629 | 9.258 |
| 266 | 510.8 | 0.004570 | 9.140 |
| 267 | 512.6 | 0.004512 | 9.024 |
| 268 | 514.4 | 0.004455 | 8.910 |
| 269 | 516.2 | 0.004399 | 8.798 |
| 270 | 518.0 | 0.004344 | 8.688 |
| 271 | 519.8 | 0.004289 | 8.578 |
| 272 | 521.6 | 0.004236 | 8.472 |
| 273 | 523.4 | 0.004183 | 8.366 |
| 274 | 525.2 | 0.004132 | 8.264 |
| 275 | 527.0 | 0.004081 | 8.162 |
| 276 | 528.8 | 0.004031 | 8.062 |
| 277 | 530.6 | 0.003982 | 7.964 |
| 278 | 532.4 | 0.003933 | 7.866 |
| 279 | 534.2 | 0.003886 | 7.772 |
| 280 | 536.0 | 0.003839 | 7.678 |
| 281 | 537.8 | 0.003793 | 7.586 |
| 282 | 539.6 | 0.003747 | 7.494 |
| 283 | 541.4 | 0.003703 | 7.406 |
| 284 | 543.2 | 0.003659 | 7.318 |
| 285 | 545.0 | 0.003615 | 7.230 |
| 286 | 546.8 | 0.003573 | 7.146 |
| 287 | 548.6 | 0.003531 | 7.062 |
| 288 | 550.4 | 0.003490 | 6.980 |
| 289 | 552.2 | 0.003449 | 6.898 |
| 290 | 554.0 | 0.003409 | 6.818 |

| Temperature (°C) | Temperature (°F) | Resistance Ratio (R@x°C / R@+25°C) | Resistance (Ω Nominal) |
|------------------|------------------|------------------------------------|------------------------|
| 291 | 555.8 | 0.003369 | 6.738 |
| 292 | 557.6 | 0.003331 | 6.662 |
| 293 | 559.4 | 0.003292 | 6.584 |
| 294 | 561.2 | 0.003255 | 6.510 |
| 295 | 563.0 | 0.003218 | 6.436 |
| 296 | 564.8 | 0.003181 | 6.362 |
| 297 | 566.6 | 0.003145 | 6.290 |
| 298 | 568.4 | 0.003110 | 6.220 |
| 299 | 570.2 | 0.003075 | 6.150 |
| 300 | 572.0 | 0.003041 | 6.082 |