

NOTES:


1. MATERIALS AND FINISHES:  
 BODY & CONTACT - BeCu, GOLD PLATING  
 REAR BODY - BRASS, GOLD PLATING  
 INSULATORS - PTFE, NATURAL  
 FERRULE - COPPER, NICKEL PLATING  
 RETAINING RING - BeCu, NICKEL PLATING
2. ELECTRICAL:  
 A. IMPEDANCE: 50 OHM  
 B. FREQUENCY RANGE: DC - 6 GHz
3. MECHANICAL:  
 A. DURABILITY: 100 CYCLES MIN.  
 B. TEMPERATURE RANGE: -65°C TO +165°C
4. PACKAGING:  
 A. QUANTITY: SINGLE PACK  
 B. MARKING: BAG TO BE MARKED  
 "AMPHENOL RF, SMP-FS-C08-1-R AND DATE CODE"  
 C. CONTACT PIN AND FERRULE ARE PACKAGED LOOSE.  
 中心针和压接套筒散装。
5. CABLE ASSEMBLY INSTRUCTIONS:  
 A. TRIM CABLE AS SHOWN.  
 B. SOLDER CABLE CENTER CONDUCTOR TO CONTACT.  
 C. CRIMP FERRULE WITH 0.128" HEX.

6 SHOWS CABLE ENTRY DIMENSIONS.


THIRD ANGLE PROJ.

REVISIONS


REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	15-Apr-15	50495	JTS
B	FREQUENCY UPDATED TO 6 GHz	17-Nov-16	02424	NR
C	DOCUMENTATION CHANGE	01-Dec-16	02641	BMG




RECOMMENDED CABLE STRIPPING DIMENSIONS



SCALE 4.000



ASSEMBLED VIEW



**CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:  
 <0.5mm ±0.05mm    0.5 - 6mm ±0.1mm    6 - 30mm ±0.2mm    30 - 120mm ±0.3mm    ANGLES ±1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL SEE NOTES	DRAWN STAR	DATE 17-Nov-16	TITLE SMP STR PLUG WITH FEMALE CONTACT FOR RG 316 CABLE	Amphenol RF www.amphenolrf.com	
REFERENCE EAR # 4720.2	ENGINEER SUNDE	DATE 22-Apr-15		DRAWING NO. SMP-FS-C08-1-R	ITEM NO. SMP-FS-C08-1-R
CONFIGURATION LEVEL: In Work	APPROVED HARRY	DATE 22-Nov-16	SCALE: 10.0:1.0 SHEET 2 OF 2	DWG SIZE B	REV C
FINISH					