


## **Specification Sheet**

Part Number: 596-00885



Solar Label, Reflective, SOLAR PV SYSTEM...SHUTDOWN, 6.0" x 4.0", V, Yellow, 50/roll

Article Number 596-00885

Type RSDYL17

Color Yellow (YE)

Features & Benefits

 Made with UV-stable inks and materials for durability and weather resistance.
 Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
 Abrasion resistant for high-performance identification.
 Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per roll

_				-	_							
ם	rn	<b>~</b> I	114	rt.	- 11	es	r	rı	n	tı	$\mathbf{a}$	'n
	v	u	и١	Ŀι	$\boldsymbol{\omega}$	CO	u		v	LI	u	

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Short Description** 

**Global Part Name** 

Solar Label, Reflective, SOLAR PV SYSTEM...SHUTDOWN, 6.0" x 4.0", V, Yellow, 50/roll

RSDYL17-505/281-YE

**Technical Description** 

Pre-Printed Solar Label, Reflective-2017 Code, Rapid Shutdown Label - Roof Safe, 6.0" X 4.0", Vinyl, Yellow, 50/RL

Length L (Imperial)

4

Length L (Metric)

101.6

Width W (Imperial)

6.0

Width W (Metric)

152.4

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

4.0

**Height H (Metric)** 

101.60

**Material** Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281) **Material Shortcut** 505/281 Adhesive Acrylic Halogen free No **Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C) **Operating Temperature (Metric)** -40°F to +174°F (-40°C to +79°C) Reach Complaint(Article 33) Yes **ROHS Complaint** Yes **Certification/Specification WEB** NEC2017 NEC2020

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity(Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

1

Labels per Column

Labels per Row 1

Weight (Metric) 0.521

Weight (Imperial) 1.14

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions