

Specification Sheet

Part Number: 596-00821

**PRECAUCIÓN: SISTEMA ELÉCTRICO
SOLAR CONECTADO**

Solar Label, Reflective, Spanish, CAUTION SOLAR ELECTRIC SYSTEM..., 6.5" x 1.0", V, Yellow, 50/roll

Article Number 596-00821

Type CSESCS

Color Yellow (YE)

Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- Abrasion resistant for high-performance identification.
- Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per roll

Product Description	HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Solar Label, Reflective, Spanish, CAUTION SOLAR ELECTRIC SYSTEM..., 6.5" x 1.0", V, Yellow, 50/roll
Global Part Name	CSESCS-505/281-YE
Technical Description	Pre-Printed Solar Label, Reflective, Spanish Version, "SOLAR ELECTRIC SYSTEM CONNECTED", 6.5" X 1.0", Yellow
Local Order Number 2	English Version: 596-00613
Length L (Imperial)	6.5
Length L (Metric)	165.1
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.0

Height H (Metric)	25.4
Material	Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281)
Material Shortcut	505/281
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2014 NEC2011
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055

Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	1.14