


**STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS****Straight Strain Relief Cord Connectors Steel/Malleable Iron**  
N/A**B57**

Catalog #: 3702-3

**APPLICATIONS**

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable  
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

**PRODUCT FEATURES**

All steel/malleable construction provides mechanical strength  
Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened for a positive liquidtight seal  
Washers have cable size range imprinted for identification - eliminates misidentifying inventory  
Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel  
All metallic components are zinc electro plated for added corrosion protection  
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation  
3/8 in. to 1 in. Steel bodies; 1-1/4 in. to 1-1/2 in. Malleable Iron bodies  
3/8 in. to 1 in. Steel nuts; 1-1/4 in. to 1-1/2 in. Malleable Iron nuts  
N/A

**CULUS**

UL File E195973

**GENERAL PRODUCT INFORMATION**

Trade Size: 1/2 in.  
Cable Range: .375 - .425  
Form Size: 1

**DRAWING DIMENSIONS**

Dimension A: 1-1/16 in.  
Dimension B: 1/2 in.  
Thread Spec. B: 1/2 in. - 14 NPT  
Dimension C: 1-29/64 in.

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 16.00  
Ship Carton Length (in.): 6.25  
Ship Carton Width (in.): 4.50  
Ship Carton Height (in.): 4.25  
Ctn Weight (Lbs.): 4.00  
UPC Number: 050169370230  
I2of5: 50050169370235