


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
B	ECN2917: UPDATED PICTORIALY. UPDATED NOTE FORMAT AND CONTENT.	07/18/07	D.PARHAM
C	ECN3191: ADDED 20, 30, 40, 60, 80 & 90 FT LENGTHS	02/06/08	D.PARHAM
D	ECN3320: ADDED PACKAGED ON A SPOOL NOTE. UPDATED FORMAT.	05/07/08	D. PARHAM
E	ECN3552: ADDED RED & BLK CABLES. MODIFIED PACKAGING NOTE.		D. PARHAM



NOTES:

MATERIAL:

PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0
 CONTACTS: PHOSPHOR BRONZE
 CABLE JACKET: LSZH COLOR: SEE SHEET 2
 PLUG SHIELDING: BRASS
 SNAGLESS BOOT: LSZH THERMOPLASTIC, BLACK

FINISH:

CONTACTS: 50 μINCHES GOLD IN CONTACT AREA
 OVER 100 μINCHES NICKEL PLATE OVERALL.
 PLUG SHIELDING: NICKEL PLATED



CABLE CHARACTERISTICS:

SHIELDING: ALUMINUM/POLYESTER AND BRAIDED TINNED COPPER
 CONDUCTORS: FOUR TWISTED PAIR, 26 AWG (7X34) STRANDED COPPER

MISCELLANEOUS:

ASSEMBLY WIRED PER 568B SEQUENCE
 PLUG CONFORMS TO TIA-1096
 OPERATING TEMPERATURE RANGE: -20°C TO +60°C
 CABLES TO BE TESTED FOR CONTINUITY
 CABLES INDIVIDUALLY PACKAGED IN A POLYBAG


RoHS Compliant ✓

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	APPROVALS	DATE	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845		
	DRAWN BY D.PARHAM	12/07/2006			
OVERALL CABLE LENGTH TOLERANCE: ≤ 12 [305] = +1 [25] / -0 >12 [305] ≤ 60 [1524] = +2[51] / -0 >60 [1524] ≤ 120 [3048] = +4 / -0 >120 [3048] ≤ 300 [7620] = +6 / -0 >300 [7620] = +5% / -0%	CHECKED BY C.McCORMICK	12/07/2006	CATEGORY		
	ALL OTHER DIMENSIONAL TOLERANCES: .X = .3 .XX = .15	APPROVED BY D.GALLAGHER	12/11/2006	TELECOM/MODULAR	
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		PRODUCT DESCRIPTION		
	COLOR VARIATIONS MAY OCCUR	SIZE A	FSCM NO. 43321	DWG. NO. TRD855DSZ	REV. E
		SCALE: NONE	CAD FILE: TRD855DSZ.SLDDRW	SHEET 1 OF 2	

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
B	ECN2917: UPDATED PICTORIALY. UPDATED NOTE FORMAT AND CONTENT.	07/18/07	D.PARHAM
C	ECN3191: ADDED 20, 30, 40, 60, 80 & 90 FT LENGTHS	02/06/08	D.PARHAM
D	ECN3320: ADDED PACKAGED ON A SPOOL NOTE. UPDATED FORMAT.	05/07/08	D. PARHAM
E	ECN3552: ADDED RED & BLK CABLES. MODIFIED PACKAGING NOTE.		D. PARHAM

PART NUMBER	JACKET COLOR	LENGTH		PART NUMBER	JACKET COLOR	LENGTH		PART NUMBER	JACKET COLOR	LENGTH	
		FEET	METERS			FEET	METERS			FEET	METERS
TRD855DSZ-1	GRAY	1.0	0.31	TRD855DSZBLK-1	BLACK	1.0	0.31	TRD855DSZRD-1	RED	1.0	0.31
TRD855DSZ-2	GRAY	2.0	0.61	TRD855DSZBLK-2	BLACK	2.0	0.61	TRD855DSZRD-2	RED	2.0	0.61
TRD855DSZ-3	GRAY	3.0	0.91	TRD855DSZBLK-3	BLACK	3.0	0.91	TRD855DSZRD-3	RED	3.0	0.91
TRD855DSZ-5	GRAY	5.0	1.52	TRD855DSZBLK-5	BLACK	5.0	1.52	TRD855DSZRD-5	RED	5.0	1.52
TRD855DSZ-7	GRAY	7.0	2.13	TRD855DSZBLK-7	BLACK	7.0	2.13	TRD855DSZRD-7	RED	7.0	2.13
TRD855DSZ-10	GRAY	10.0	3.05	TRD855DSZBLK-10	BLACK	10.0	3.05	TRD855DSZRD-10	RED	10.0	3.05
TRD855DSZ-15	GRAY	15.0	4.57	TRD855DSZBLK-15	BLACK	15.0	4.57	TRD855DSZRD-15	RED	15.0	4.57
TRD855DSZ-20	GRAY	20.0	6.10	TRD855DSZBLK-20	BLACK	20.0	6.10	TRD855DSZRD-20	RED	20.0	6.10
TRD855DSZ-25	GRAY	25.0	7.62	TRD855DSZBLK-25	BLACK	25.0	7.62	TRD855DSZRD-25	RED	25.0	7.62
TRD855DSZ-30	GRAY	30.0	9.14	TRD855DSZBLK-30	BLACK	30.0	9.14	TRD855DSZRD-30	RED	30.0	9.14
TRD855DSZ-40	GRAY	40.0	12.19	TRD855DSZBLK-40	BLACK	40.0	12.19	TRD855DSZRD-40	RED	40.0	12.19
TRD855DSZ-50	GRAY	50.0	15.24	TRD855DSZBLK-50	BLACK	50.0	15.24	TRD855DSZRD-50	RED	50.0	15.24
TRD855DSZ-60	GRAY	60.0	18.29	TRD855DSZBLK-60	BLACK	60.0	18.29	TRD855DSZRD-60	RED	60.0	18.29
TRD855DSZ-75	GRAY	75.0	22.86	TRD855DSZBLK-75	BLACK	75.0	22.86	TRD855DSZRD-75	RED	75.0	22.86
TRD855DSZ-80	GRAY	80.0	24.38	TRD855DSZBLK-80	BLACK	80.0	24.38	TRD855DSZRD-80	RED	80.0	24.38
TRD855DSZ-90	GRAY	90.0	27.43	TRD855DSZBLK-90	BLACK	90.0	27.43	TRD855DSZRD-90	RED	90.0	27.43
TRD855DSZ-100	GRAY	100.0	30.48	TRD855DSZBLK-100	BLACK	100.0	30.48	TRD855DSZRD-100	RED	100.0	30.48
TRD855DSZ-150	GRAY	150.0	45.72	TRD855DSZBLK-150	BLACK	150.0	45.72	TRD855DSZRD-150	RED	150.0	45.72
TRD855DSZ-200	GRAY	200.0	60.96	TRD855DSZBLK-200	BLACK	200.0	60.96	TRD855DSZRD-200	RED	200.0	60.96
TRD855DSZ-250	GRAY	250.0	76.20	TRD855DSZBLK-250	BLACK	250.0	76.20	TRD855DSZRD-250	RED	250.0	76.20
TRD855DSZ-300	GRAY	300.0	91.44	TRD855DSZBLK-300	BLACK	300.0	91.44	TRD855DSZRD-300	RED	300.0	91.44

<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]</p> <p>OVERALL CABLE LENGTH TOLERANCE: ≤ 12 [305] = +1 [25] / -0 >12 [305] ≤ 60 [1524] = +2 [51] / -0 >60 [1524] ≤ 120 [3048] = +4 [102] / -0 >120 [3048] ≤ 300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%</p> <p>ALL OTHER DIMENSIONAL TOLERANCES: .X = .3 .XX = .15</p> <p>PROJECTION </p>	<p>APPROVALS</p> <p>DRAWN BY D.PARHAM</p> <p>CHECKED BY C.McCORMICK</p> <p>APPROVED BY D.GALLAGHER</p>	<p>DATE</p> <p>12/07/2006</p> <p>12/07/2006</p> <p>12/11/2006</p>	<p>L-com CONNECTIVITY PRODUCTS</p> <p>45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845</p>	
	<p>CATEGORY</p> <p>TELECOM/MODULAR</p>		<p>PRODUCT DESCRIPTION</p> <p>CATEGORY 5e PATCH CORD, LSZH</p>	
	<p>CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY</p> <p>COLOR VARIATIONS MAY OCCUR</p>	<p>SIZE</p> <p>A</p>	<p>FSCM NO.</p> <p>43321</p>	<p>DWG. NO.</p> <p>TRD855DSZ</p>
	<p>SCALE: NONE</p>		<p>CAD FILE: TRD855DSZ.SLDRW</p>	<p>REV.</p> <p>E</p>