




AC CABLE DUPLEX CONNECTORS

90° Squeeze Connectors, Uninsulated Die Cast Zinc
N/A

B69.1



Catalog #: 2693

APPLICATIONS

- For use in dry locations to bond flexible metal conduit to a box or enclosure
- N/A
- For use in dry locations to bond armored cable to a box or enclosure

PRODUCT FEATURES

Rugged metallic construction insures mechanical protection for the raceway

UL LISTED

Standard 514B, File E195969

CSA

C22.2 No. 18

GENERAL PRODUCT INFORMATION

Trade Size: 3/4 in.

DRAWING DIMENSIONS

- Dimension A: 7/16 in.
- Dimension B: 2-3/32 in.
- Dimension C: 63/64 in. - 1-13/32 in.
- Dimension D: NO. 8x5/8 in.
- Dimension E: 3/4 in. - 14 NPSM

PACKAGING

- Package Type: Carton
- Std. Pkg.: 10
- Ship Carton Qty.: 100
- Product UPC-A Labeled: No
- Weight (Lbs. Per/C): 18.20
- Ship Carton Length (in.): 19.00
- Ship Carton Width (in.): 10.62
- Ship Carton Height (in.): 5.31
- Ctn Weight (Lbs.): 19.20
- UPC Number: 050169026939
- I2of5: 50050169026934