# B-155-3813 ✓ ACTIVE

### Raychem

TE Internal #: C97376-000

SolderSleeve Shield Terminators, Operating Temperature (Max)

125 °C, Expanded Inside Diameter (Min) 13 mm [.51 in]

View on TE.com >



Harnessing > Interconnect Devices > SolderSleeve Shield Terminators



Operating Temperature (Max): 125 °C

Expanded Inside Diameter (Min): 13 mm [ .51 in ]

Recovered Inside Diameter (Max): 8.9 mm [ .35 in ]

Pre-Installed Lead: No

Wire Temperature (Max): 85 °C

## **Features**

## **Configuration Features**

Pre-Installed Lead	No
Dimensions	
Expanded Inside Diameter (Min)	13 mm[.51 in]
Recovered Inside Diameter (Max)	8.9 mm[.35 in]
Usage Conditions	
Operating Temperature (Max)	125 °C
Wire Temperature (Max)	85 °C

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# **Customers Also Bought**











## **Documents**

Product Drawings B-155-3813

English

SolderSleeve Shield Terminators, Operating Temperature (Max) 125 °C, Expanded Inside Diameter (Min) 13 mm [.51 in]



Datasheets & Catalog Pages

Raychem Electrical Interconnect Products

English