


LUTZE TOP-T Fittings Enlargers

Metal PG and Metric Enlargers



Characteristics

- Reduction of threaded or clearance holes to larger thread size

Specifications

Internal/External thread	PG DIN 40430 Metric EN 60423
Temperature range	up to +200°C/+392°F
Material	Brass, nickel plated

Locknuts sold separately.

Specifications are subject to change without prior notice

Part No.	Thread A	Thread B	L mm	H mm	Da mm	Di mm
PG						
EMPG7-9	PG 7	PG 9	5	15	17	8
EMPG9-11	PG 7	PG 11	6	16.5	20	11.7
EMPG11-13	PG 11	PG 13.5	6	17.5	22	13.8
EMPG13-16	PG 13.5	PG 16	6.5	17	24	16.4
EMPG16-21	PG 16	PG 21	6.5	18.5	29.7	17.6
EMPG21-29	PG 21	PG 29	7	23	39	24
EMPG29-36	PG 29	PG 36	8	27.5	50	32
EMPG36-42	PG 36	PG 42	9	31	57	38
METRIC						
EMM12-16	M12x1.5	M16x1.5	6	15	18	8
EMM16-20	M16x1.5	M20x1.5	6	17.6	22	12
EMM20-25	M20x1.5	M25x1.5	7	17.5	27	16
EMM25-32	M25x1.5	M32x1.5	8	19.5	34	20.5
EMM32-40	M32x1.5	M40x1.5	8	22.5	42	26