


LUTZE TOP-T Fittings Reducer

Metal PG and Metric Reducer



Characteristics

- Reduction of threaded or clearance holes to smaller thread size

Specifications

Internal/External thread	PG DIN 40430 Metric EN 60423
Temperature range	up to +200°C/+392°F
Material	Brass, nickel plated

Locknuts sold separately.

Specifications are subject to change without prior notice

Part No.	Thread G	Thread G1	SW mm	L mm	L1 mm
PG					
RMPG11-7	PG 11	PG 7	20	9	6
RMPG11-9	PG 11	PG 9	20	9	6
RMPG13-9	PG 13.5	PG 9	22	9	6.5
RMPG13-11	PG 13.5	PG 11	22	9	6.5
RMPG16-9	PG 16	PG 9	24	9.5	6.5
RMPG16-11	PG 16	PG 11	24	9	6
RMPG16-13	PG 16	PG 13.5	24	9	6
RMPG21-11	PG 21	PG 11	30	10	7
RMPG21-13	PG 21	PG 13.5	30	10	7
RMPG21-16	PG 21	PG 16	30	10	7
RMPG29-16	PG 29	PG 16	39	11.5	8
RMPG29-21	PG 29	PG 21	39	11.4	8
RMPG36-21	PG 36	PG 21	50	12.4	9
RMPG36-29	PG 36	PG 29	50	12.5	9.1
RMPG42-36	PG 42	PG 36	57	14.1	10
METRIC					
RMM16-12	M16x1.5	M12x1.5	18	9.5	6.5
RMM20-12	M20x1.5	M12x1.5	22	9.5	6.5
RMM20-16	M20x1.5	M16x1.5	22	9	6.5
RMM25-16	M25x1.5	M16x1.5	28	9	6.5
RMM25-20	M25x1.5	M20x1.5	30	11.5	8
RMM32-20	M32x1.5	M20x1.5	39	11.5	8
RMM32-25	M32x1.5	M25x1.5	39	11.5	8
RMM40-25	M40x1.5	M25x1.5	50	12.5	9
RMM40-32	M40x1.5	M32x1.5	50	12.5	9
RMM50-32	M50x1.5	M32x1.5	64	14	10
RMM50-40	M50x1.5	M40x1.5	64	14	10