

1SNL317531R0000 ✓ ACTIVE

ENTRELEC

TE Internal #: 1SNL317531R0000

Power Distribution Blocks, 3x1 Pole, 175A Current Rating (IEC),
175A Current Rating (UL), 8 Position, Wire & Cable, 175A Contact
Current Rating (Max)

[View on TE.com >](#)



Connectors > Terminal Blocks & Strips > Power Distribution Blocks



Circuit Configuration: **3x1 Pole**

Current Rating (IEC): **175 A**

Current Rating (UL): **175 A**

Number of Positions: **8**

Sealable: **No**

Features

Product Type Features

Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Poles - Main Circuit	1
Block Configuration	Feed-Through
Number of Poles - Output 1	1
Number of Poles - Output 2	6
Number of Levels	1
Number of Circuits	1
Circuit Configuration	3x1 Pole
Number of Positions	8

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	1000 V
Voltage Rating (CSA)	1000 V
Peak Withstanding Current Rating	30 kA
Voltage Rating (IEC)	1500 VDC



Dielectric Test Voltage	2200 V
Power Loss	16.8 W
Input Current (Max)	175 A
Current Rating (IEC)	175 A
Current Rating (UL)	175 A

Body Features

Product Weight	360 g[12.698 oz]
----------------	------------------

Contact Features

Contact Current Rating (Max)	175 A
------------------------------	-------

Mechanical Attachment

Tightening Torque - Output 1	18 – 26.5 in-lbs
DIN Rail Mounting Type	TH35-15, TH35-7.5
Connection Type	Screw
Tightening Torque - Main Circuit	53 – 88 in-lbs
Tightening Torque - Output 2	18 – 26.5 in-lbs
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
Housing Color	Gray

Dimensions

Output 1 Capacity - 1 Insulated Ferrule	14 – 6 AWG
Output 2 Capacity - 1 Insulated Ferrule	14 – 6 AWG
Output 2 Capacity - 1 Rigid Stranded Conductor	14 – 6 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	16 – 50 mm ²
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	6 – 00 AWG
Output 1 Capacity - 1 Rigid Stranded Conductor	6 – 16 mm ²
Wire Stripping Length - Output 1	11 mm[.43 in]
Wire Stripping Length - Main Circuit	18 mm[.709 in]
Tool Size - Output 2	5.5 mm[.217 in]
Hole Diameter - Output 1	6.8 mm[.267 in]
Hole Diameter - Output 2	6.5 mm[.256 in]
Tool Size - Output 1	3 mm[.118 in]



Hole Diameter - Main Circuit	11.8 mm[.465 in]
Wire Stripping Length - Output 2	11 mm[.43 in]
Tool Size - Main Circuit	5 mm[.197 in]
Product Spacing	84.6 mm[3.33 in]
Rated Cross Section	0 AWG
Product Depth	50.7 mm[1.788 in]
Product Width	84.6 mm[2.984 in]
Product Height	75 mm[2.645 in]

Usage Conditions

Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Tool - Output 2	Positive Drive Flat Screwdriver
Tool - Output 1	Allen Key
Tool - Main Circuit	Allen Key
IP Rating	IP10
UL Flammability Rating	UL 94V-0

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 <p>TE Model / Part # 1SNK900102R0000 BAZH1</p>	 <p>TE Model / Part # 1SNK149999R0000 MC512PA</p>	 <p>TE Model / Part # 1SNK140000R0000 MC512</p>	 <p>TE Model / Part # 1SNK900002R0000 BAZ1</p>
 <p>TE Model / Part # 1SNK900001R0000 BAM4</p>	 <p>TE Model / Part # 1SNK149002R0000 MC512PA L1-L2-L3-N-PE (x20) Vertical</p>	 <p>TE Model / Part # 1SNA116900R2700 BADH</p>	 <p>TE Model / Part # 1SNA399903R0200 BADL</p>
 <p>TE Model / Part # 1SNB041790R0512 MG-CPM-13 41790 (5X12 WH)</p>			

Customers Also Bought



TE Model / Part #1-1879363-6
THS75 510R 5%



TE Model / Part #2151047-2
OCEAN_2.0_APPLICATOR-S-100F140O



TE Model / Part #2151067-2
OCEAN_2.0_APPLICATOR-S-100F140O



TE Model / Part #1SNL325060R0000
DBL250-F




TE Model / Part #6-2176244-3
CRGS0805 5% 150K



TE Model / Part #5-2176244-9
CRGS0805 5% 68K



TE Model / Part #1969796-1
02P UMNL HDR ASSY R/A, PIN V0 GW



TE Model / Part #2-1825138-2
A201SYAB04



TE Model / Part #3-1825139-2
A211P3ZQ04



TE Model / Part #5-2176244-8
CRGS0805 5% 56K

Documents

Datasheets & Catalog Pages

[ENTRELEC DBL Power Distribution Blocks Catalogue](#)

English

[ENTRELEC Terminal Block - Master Catalog](#)

English

[DBL175-C-3](#)

English

Agency Approvals

[CE Declaration of Conformity](#)

English