


# LUTZE TOP-T Fittings Enlargers

## Metal PG and Metric Enlargers



### Characteristics

- Reduction of threaded or clearance holes to larger thread size

### Specifications

Internal/External thread	PG DIN 40430 Metric EN 60423
Temperature range	up to +200°C/+392°F
Material	Brass, nickel plated

Locknuts sold separately.

Specifications are subject to change without prior notice

Part No.	Thread A	Thread B	L mm	H mm	Da mm	Di mm
<b>PG</b>						
<b>EMPG7-9</b>	PG 7	PG 9	5	15	17	8
<b>EMPG9-11</b>	PG 7	PG 11	6	16.5	20	11.7
<b>EMPG11-13</b>	PG 11	PG 13.5	6	17.5	22	13.8
<b>EMPG13-16</b>	PG 13.5	PG 16	6.5	17	24	16.4
<b>EMPG16-21</b>	PG 16	PG 21	6.5	18.5	29.7	17.6
<b>EMPG21-29</b>	PG 21	PG 29	7	23	39	24
<b>EMPG29-36</b>	PG 29	PG 36	8	27.5	50	32
<b>EMPG36-42</b>	PG 36	PG 42	9	31	57	38
<b>METRIC</b>						
<b>EMM12-16</b>	M12x1.5	M16x1.5	6	15	18	8
<b>EMM16-20</b>	M16x1.5	M20x1.5	6	17.6	22	12
<b>EMM20-25</b>	M20x1.5	M25x1.5	7	17.5	27	16
<b>EMM25-32</b>	M25x1.5	M32x1.5	8	19.5	34	20.5
<b>EMM32-40</b>	M32x1.5	M40x1.5	8	22.5	42	26