


# LUTZE TOP-T Fittings PG

## Plastic PG



### Characteristics

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Manufactured acc to EN 62444

### Specifications

Connecting thread	PG DIN 40430
Temperature range	
Permanent	-20°C - +100°C / -4°F - +212°F
Intermittent	-30°C - +150°C / -22°F - +302°F
Protection class	IP68 EN 60529
Material	
Body	Polyamide 6
Seal	CR Chloroprene Rubber
Color	Black RAL 9005 Gray RAL 7001

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm	UL R / L
<b>BLACK</b>								
FPPG7B	PG 7	0.118-0.256	3-6.5	8	15	12.5	22	R
FPPG9B	PG 9	0.157-0.315	4-8	8	19	15.2	26.5	R
FPPG11B	PG 11	0.197-0.394	5-10	8	22	18.6	29	R
FPPG13B	PG 13.5	0.236-0.472	6-12	10	24	20.4	29	L
FPPG16B	PG 16	0.394-0.551	10-14	10	27	22.5	31	L
FPPG21B	PG 21	0.512-0.709	13-18	11	33	28.3	37	L
FPPG29B	PG 29	0.709-0.984	18-25	11	42	37	41	L
FPPG36B	PG 36	0.866-1.260	22-32	13	53	47	51.5	L
FPPG42B	PG 42	1.181-1.496	30-38	13	60	54	53.5	L
FPPG48B	PG 48	1.339-1.732	34-44	14	65	59.3	53.5	L
<b>GRAY</b>								
FPPG7G	PG 7	0.118-0.256	3-6.5	8	15	12.5	22	R
FPPG9G	PG 9	0.157-0.315	4-8	8	19	15.2	26.5	R
FPPG11G	PG 11	0.197-0.394	5-10	8	22	18.6	29	R
FPPG13G	PG 13.5	0.236-0.472	6-12	10	24	20.4	29	L
FPPG16G	PG 16	0.394-0.551	10-14	10	27	22.5	31	L
FPPG21G	PG 21	0.512-0.709	13-18	11	33	28.3	37	L
FPPG29G	PG 29	0.709-0.984	18-25	11	42	37	41	L
FPPG36G	PG 36	0.866-1.260	22-32	13	53	47	51.5	L
FPPG42G	PG 42	1.181-1.496	30-38	13	60	54	53.5	L
FPPG48G	PG 48	1.339-1.732	34-44	14	65	59.3	53.5	L

### Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table

Locknuts sold separately.

Specifications are subject to change without prior notice