


LUTZE TOP-T Fittings Metric



Characteristics

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- Manufactured acc to EN 62444

Specifications

Connecting thread	Metric EN 60423
Temperature range	
Permanent	-20°C - +100°C / -4°F - +212°F
Intermittent	-30°C - +150°C / -22°F - +302°F
Protection class	IP68 EN 60529
Material	
Body	Polyamide 6
Seal	CR Chloroprene Rubber
Color	Black RAL 9005 Gray RAL 7001

Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	D/SW mm	TD mm	H mm	UL R / L
BLACK								
FPM12B	M12x1.5	0.118-0.256	3-6.5	8	15	12	22.5	R
FPM16B	M16x1.5	0.197-0.394	5-10	10	22	16	30	R
FPM20B	M20x1.5	0.315-0.551	10-14	10	27	20	31	L
FPM25B	M25x1.5	0.512-0.709	13-18	10	33	25	37	L
FPM32B	M32x1.5	0.709-0.984	18-25	15	42	32	41	L
FPM40B	M40x1.5	0.866-1.260	22-32	18	53	40	51.5	L
FPM50B	M50x1.5	1.181-1.496	30-38	18	60	50	53	L
FPM63B	M63x1.5	1.339-1.732	34-44	18	65	63	53	L
GRAY								
FPM12G	M12x1.5	0.118-0.256	3.0-6.5	8	15	12	22.5	R
FPM16G	M16x1.5	0.197-0.394	5-10	10	22	16	30	R
FPM20G	M20x1.5	0.315-0.551	10-14	10	27	20	31	L
FPM25G	M25x1.5	0.512-0.709	13-18	10	33	25	37	L
FPM32G	M32x1.5	0.709-0.984	18-25	15	42	32	41	L
FPM40G	M40x1.5	0.866-1.260	22-32	18	53	40	51.5	L
FPM50G	M50x1.5	1.181-1.496	30-38	18	60	50	53	L
FPM63G	M63x1.5	1.339-1.732	34-44	18	65	63	53	L
REDUCED CLAMPING RANGE								
FPM16G-R	M16x1.5	0.118-0.276	3-7	10	22	16	30	R
FPM20G-R	M20x1.5	0.276-0.472	7-12	10	27	20	31	L
FPM25G-R	M25x1.5	0.354-0.630	9-16	10	33	25	37	L
FPM32G-R	M32x1.5	0.472-0.787	12-20	15	42	32	41	L

Locknuts sold separately.

Specifications are subject to change without prior notice