


# LUTZE TOP-T Fittings Reducer

## Metal PG and Metric Reducer



### Characteristics

- Reduction of threaded or clearance holes to smaller thread size

### Specifications

Internal/External thread	PG DIN 40430 Metric EN 60423
Temperature range	up to +200°C/+392°F
Material	Brass, nickel plated

Locknuts sold separately.

Specifications are subject to change without prior notice

Part No.	Thread G	Thread G1	SW mm	L mm	L1 mm
<b>PG</b>					
<b>RMPG11-7</b>	PG 11	PG 7	20	9	6
<b>RMPG11-9</b>	PG 11	PG 9	20	9	6
<b>RMPG13-9</b>	PG 13.5	PG 9	22	9	6.5
<b>RMPG13-11</b>	PG 13.5	PG 11	22	9	6.5
<b>RMPG16-9</b>	PG 16	PG 9	24	9.5	6.5
<b>RMPG16-11</b>	PG 16	PG 11	24	9	6
<b>RMPG16-13</b>	PG 16	PG 13.5	24	9	6
<b>RMPG21-11</b>	PG 21	PG 11	30	10	7
<b>RMPG21-13</b>	PG 21	PG 13.5	30	10	7
<b>RMPG21-16</b>	PG 21	PG 16	30	10	7
<b>RMPG29-16</b>	PG 29	PG 16	39	11.5	8
<b>RMPG29-21</b>	PG 29	PG 21	39	11.4	8
<b>RMPG36-21</b>	PG 36	PG 21	50	12.4	9
<b>RMPG36-29</b>	PG 36	PG 29	50	12.5	9.1
<b>RMPG42-36</b>	PG 42	PG 36	57	14.1	10

<b>METRIC</b>					
<b>RMM16-12</b>	M16x1.5	M12x1.5	18	9.5	6.5
<b>RMM20-12</b>	M20x1.5	M12x1.5	22	9.5	6.5
<b>RMM20-16</b>	M20x1.5	M16x1.5	22	9	6.5
<b>RMM25-16</b>	M25x1.5	M16x1.5	28	9	6.5
<b>RMM25-20</b>	M25x1.5	M20x1.5	30	11.5	8
<b>RMM32-20</b>	M32x1.5	M20x1.5	39	11.5	8
<b>RMM32-25</b>	M32x1.5	M25x1.5	39	11.5	8
<b>RMM40-25</b>	M40x1.5	M25x1.5	50	12.5	9
<b>RMM40-32</b>	M40x1.5	M32x1.5	50	12.5	9
<b>RMM50-32</b>	M50x1.5	M32x1.5	64	14	10
<b>RMM50-40</b>	M50x1.5	M40x1.5	64	14	10