


LUTZE TOP-T Fittings PG

Metal PG



Characteristics

- Integrated strain relief
- Anti-twist design
- Wide sealing and clamping range
- Easy to install

Specifications

Connecting thread	PG DIN 40430
Temperature range	
Permanent	-20°C - +100°C / -4°F - +212°F
Intermittent	-40°C - +150°C / -40°F - +302°F
Protection class	IP68 EN 60529
Material	
Body	Brass, nickel plated
Seal	CR Chloroprene
O-ring	Rubber
	NBR

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	SW1 mm	SW2 mm	H mm	UL R / L
PG								
FMPG7	PG 7	0.118-0.256	3-6.5	6	14	14	22	R
FMPG9	PG 9	0.157-0.315	4-8	6	17	17	23.5	R
FMPG11	PG 11	0.197-0.394	5-10	6	20	20	26	R
FMPG13	PG 13.5	0.236-0.472	6-12	6.5	22	22	24.5	L
FMPG16	PG 16	0.394-0.551	10-14	6.5	24	24	28	L
FMPG21	PG 21	0.512-0.709	13-18	7.2	30	30	32.5	L
FMPG29	PG 29	0.709-0.984	18-25	8	40	40	38.5	L
FMPG36	PG 36	0.866-1.260	22-32	9	50	50	48	L
FMPG42	PG 42	1.181-1.496	30-38	12	58	58	48.5	L
FMPG48	PG 48	1.339-1.732	34-44	14	64	64	53	L
LONG THREAD								
FMPG7-L	PG 7	0.118-0.256	3-6.5	10	14	14	22	R
FMPG9-L	PG 9	0.157-0.315	4-8	10	17	17	23.5	R
FMPG11-L	PG 11	0.197-0.394	5-10	10	20	20	26	R
FMPG13-L	PG 13.5	0.236-0.472	6-12	10	22	22	26.5	L
FMPG16-L	PG 16	0.394-0.551	10-14	10	24	24	28	L
FMPG21-L	PG 21	0.512-0.709	13-18	12	30	30	32.5	L
FMPG29-L	PG 29	0.709-0.984	18-25	12	40	40	38.5	L

Item Specific Approvals

- UL Recognized (R) or UL Listed (L), as per table
- Type 4X for UL Listed items

Locknuts sold separately.

Specifications are subject to change without prior notice