


LUTZE TOP-T Fittings Reducer

Metal PG and Metric Reducer



Characteristics

- Reduction of threaded or clearance holes to smaller thread size

Specifications

| | |
|--------------------------|---------------------------------|
| Internal/External thread | PG DIN 40430 Metric EN 60423 |
| Temperature range | up to +200°C/+392°F |
| Material | Brass, nickel plated |

Locknuts sold separately.

Specifications are subject to change without prior notice

| Part No. | Thread G | Thread G1 | SW mm | L mm | L1 mm |
|------------------|-------------|--------------|----------|---------|----------|
| PG | | | | | |
| RMPG11-7 | PG 11 | PG 7 | 20 | 9 | 6 |
| RMPG11-9 | PG 11 | PG 9 | 20 | 9 | 6 |
| RMPG13-9 | PG 13.5 | PG 9 | 22 | 9 | 6.5 |
| RMPG13-11 | PG 13.5 | PG 11 | 22 | 9 | 6.5 |
| RMPG16-9 | PG 16 | PG 9 | 24 | 9.5 | 6.5 |
| RMPG16-11 | PG 16 | PG 11 | 24 | 9 | 6 |
| RMPG16-13 | PG 16 | PG 13.5 | 24 | 9 | 6 |
| RMPG21-11 | PG 21 | PG 11 | 30 | 10 | 7 |
| RMPG21-13 | PG 21 | PG 13.5 | 30 | 10 | 7 |
| RMPG21-16 | PG 21 | PG 16 | 30 | 10 | 7 |
| RMPG29-16 | PG 29 | PG 16 | 39 | 11.5 | 8 |
| RMPG29-21 | PG 29 | PG 21 | 39 | 11.4 | 8 |
| RMPG36-21 | PG 36 | PG 21 | 50 | 12.4 | 9 |
| RMPG36-29 | PG 36 | PG 29 | 50 | 12.5 | 9.1 |
| RMPG42-36 | PG 42 | PG 36 | 57 | 14.1 | 10 |
| METRIC | | | | | |
| RMM16-12 | M16x1.5 | M12x1.5 | 18 | 9.5 | 6.5 |
| RMM20-12 | M20x1.5 | M12x1.5 | 22 | 9.5 | 6.5 |
| RMM20-16 | M20x1.5 | M16x1.5 | 22 | 9 | 6.5 |
| RMM25-16 | M25x1.5 | M16x1.5 | 28 | 9 | 6.5 |
| RMM25-20 | M25x1.5 | M20x1.5 | 30 | 11.5 | 8 |
| RMM32-20 | M32x1.5 | M20x1.5 | 39 | 11.5 | 8 |
| RMM32-25 | M32x1.5 | M25x1.5 | 39 | 11.5 | 8 |
| RMM40-25 | M40x1.5 | M25x1.5 | 50 | 12.5 | 9 |
| RMM40-32 | M40x1.5 | M32x1.5 | 50 | 12.5 | 9 |
| RMM50-32 | M50x1.5 | M32x1.5 | 64 | 14 | 10 |
| RMM50-40 | M50x1.5 | M40x1.5 | 64 | 14 | 10 |