



Family

Catalog Number: **BVNV-N069**
Product ID: 7TAA292150R0292
UPC Number: 78620995249
EAN Number: 07630030231650
Status: A

PMAFIX Straight Black Connector with NPT Threads, Material - Polyamide 6, Thread Size - 1 Inch, Conduit Size NW - 29

- Extremely high impact resistance
- Vibration proof connection to PMAFLEX conduits
- Easy installation
- High conduit pull-out strength
- Very good chemical properties
- Free from halogens and cadmium
- Fits both conduit profiles - Fine (T) and coarse (G)

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Type	Fittings for Nylon Flexible Conduits
Application	For Cable Protection Systems In a Wide Range of Applications
Standard	CSA
Size	NW29 ; 1 Inch Thread
Material	Polyamide 6
Insulation Class	IP68
Color	Black
Temperature Rating	-40 to 105 C ; Short Term to 160 C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	32mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	NPT
Thread connection size	Other
Thread material	Polyamide
Thread length	15mm
Total length	56mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N



Operating temperature -40 - +105°C

Packaging

Inner Quantity	20
Outer Quantity	100
Outer Dimensions (inches)	15.748x11.811x7.874
Weight Uom	0.06 lbs. Each

Header

3D Model Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com