AMP | AMP Type III+

TE Internal #: 1-66103-4

AMP Type III+, Power Contacts, Contact, Precious Metal, 24 – 20AWG Wire Size, .2 – .6mm² Wire Size, Wire & Cable, Crimp

View on TE.com >



Connectors > Power Connectors > Power Contacts



Power Contact Type: Contact

Contact Mating Area Plating Material: Precious Metal

Wire Size: .2 – .6 mm²

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

Power Contact Type

Connector & Contact Terminates To	Wire & Cable
Electrical Characteristics	
Test Current	13 A
Contact Features	
Contact Mating Area Plating Material	Precious Metal
Contact Current Rating (Max)	13 A
Contact Type	Pin
Mating Pin Diameter	1.57 mm[.062 in]
Contact Base Material	Brass
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Wire Contact Termination Area Plating Material Thickness	.25 μm[10 μin]
Wire Contact Termination Area Plating Material	Gold
Wire Contact Termination Area Plating Material Finish	Matte
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Size	16

Contact



Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	.2 – .6 mm²
Accepts Wire Insulation Diameter Range	1.02 – 2.03 mm[.04 – .08 in]
Usage Conditions	
Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Method	Box, Loose Piece
Packaging Quantity	100
Other	
Wire/Cable Type	Discrete Wire
For Use With	CPC Connectors, G Series Connectors, M Series Connectors

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




















Also in the Series | AMP Type III+





Customers Also Bought



TE Model / Part #3-1532183-0 M83513/03-E14C, MCKS-C2-B-31P6G9-72.0











TE Model / Part #YDTS26T19-35PNV001 PLUG ASSY











Documents

Product Drawings

III+ PIN,24-20,30AU>10,SMPACK

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-66103-4_AL.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-66103-4_AL.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-66103-4_AL.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

AMP Type III+, Power Contacts, Contact, Precious Metal, 24-20AWG Wire Size, .2-.6mm² Wire Size, Wire & Cable, Crimp



Product Specifications

Product Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

Japanese