1-1825910-0 V ACTIVE

Alcoswitch

TE Internal #: 1-1825910-0

Tactile Switches, Round Actuator Style, Operating Function NO, Brass, Silver, Low Profile, 50mA Tactile Switch Contact Current

Rating

View on TE.com >



Relays, Contactors & Switches > Switches > Tactile Switches



Actuator Style: Round
Operating Function: NO
Contact Base Material: Brass

Switch Contact Plating Material: Silver

Dust Proof: No

Features

Product Type Features

Product Type	Switch
Leg Style	Kinked
Illuminated	With
Actuator Style	Round
Dust Proof	No

Configuration Features

ESD Grounding Terminal Without	
Ganged With	
Tactile	
Snap Action Without	
Operating Function NO	
Support Bracket Without	
Configuration (Pole-Throw) Single Pole - Single Throw	
Number of Actuators 1	

Electrical Characteristics

Tactile Switch Voltage Rating	24 VDC
-------------------------------	--------

Body Features



Cover Material	PET Film
Case Color	Black
Actuator Force	160 g[5.648 oz]
Case Material	Nylon
Bushing Style	Unthreaded
Actuator Profile	Extended
Actuator Material	Nylon
Actuator Color	Blue
Contact Features	
Contact Base Material	Brass
Switch Contact Plating Material	Silver
Tactile Switch Contact Current Rating	50 mA
Termination Features	
Termination Type	Printed Circuit Board
Mechanical Attachment	
Tactile Switch Mounting Type	Through Hole
Tactile Switch Mounting Angle	Vertical
Housing Features	
Low Profile	With
Process Sealed	No
Dimensions	
Actuator Length	3.4 mm[.134 in]
Button Width	3.3 mm[.13 in]
	.276 in
Usage Conditions	
Temperature Rating	High °C
Packaging Features	
Packaging Method	Loose Piece
Other	
Comment	(On) indicates momentary position.

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





FSM4JSMATR=TACT SWITCH 6X6MIL





TE Model / Part # 2-1977223-8
FSM14JSMAS=6MM TACT SWITCH,
SMT 160gf



Customers Also Bought







MICRO USB, TYPE B,





BMB-L 0805 1K









Documents

Product Drawings

FSM6JH=6MM TACT SWITCH, HIGH TEMP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1825910-0_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1825910-0_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1825910-0_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Tactile Switches, Round Actuator Style, Operating Function NO, Brass, Silver, Low Profile, 50mA Tactile Switch Contact Current Rating



Datasheets & Catalog Pages
SWITCHES_CORE_PROGRAM_CATALOG

English

Product Environmental Compliance

TE Material Declaration

English