



Family

Catalog Number: Product ID: UPC Number: EAN Number: Status:

BVND-N076GT

7TAA292150R0166 78620995128 07630030213700 A

PMAFIX Straight Black Connector with NPT Threads and Universal Safety Clip, Material - Polyamide 6, Thread Size - 1-1/4 Inch, Conduit Size NW - 36

- Very high impact resistance
- Vibration proof connection to PMAFLEX conduits
- High conduit pull-out strength
- Very good chemical properties
- Free from halogens and cadmium
- Fits both conduit profiles Fine (T) and coarse (G)
- Easy installation, simply push the conduit in
- Can be easily re-opened with a screwdriver

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Туре	Connectors-Straight
Application	For Cable Protection Systems In a Wide Range of
	Applications
Standard	CSA
Size	NW36; 1-1/4 Inch Thread
Material	Polyamide 6
Insulation Class	IP66
Color	Black
Temperature Rating	-40 to 105 C ; Short Term to 160 C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic
	hose
Nominal diameter	40mm
Degree of protection (IP)	IP66
Model	Straight
Revolving thread	Ν
Construction type	Internal thread
Type of connection	Snap connection
Thread type	NPT
Thread connection size	Other
Thread material	Polyamide
Thread length	18mm
Total length	71mm
Material	Polyamide
Material sealing	No sealing
Colour	Black
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UR	Y
Approved in combination with protective conduit DIN EN 61386-23	Ν
	Ν



Approved in combination with protective conduit Lloyd's Register		
Operating temperature	-40 - +105°C	
Packaging		
Inner Quantity	20	
Outer Quantity	60	
Outer Dimensions (inches)	15.748x11.811x7.874	
Weight Uom	10.5 lbs. per 100	

Header

3D Model

Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com